

Stages Built Into NetRexx Pipelines 4.05 & CMS Pipelines V7R1 and Their Differences

How to Read Syntax Diagrams

Special diagrams (often called railroad tracks) are used to show the syntax of external interfaces.

To read a syntax diagram, follow the path of the line. Read from left to right and top to bottom.

- The **▶▶---** symbol indicates the beginning of the syntax diagram.
- The **---▶** symbol, at the end of a line, indicates that the syntax diagram is continued on the next line.
- The **▶---** symbol, at the beginning of a line, indicates that the syntax diagram is continued from the previous line.
- The **---▶◀** symbol indicates the end of the syntax diagram.

Within the syntax diagram, items on the line are required, items below the line are optional, and items above the line are defaults.

Pipelines Builtin Stages

Show Stages Implemented in: <input checked="" type="checkbox"/> NetRexx Pipelines: <input checked="" type="checkbox"/> CMS Pipelines:
Show All Details: <input checked="" type="checkbox"/> (Double click on a row to turn it on/off.)
<input checked="" type="checkbox"/> Highlight NetRexx Only / CMS Only:
Show Only Changes: <input checked="" type="radio"/> None <input type="radio"/> 4.05 <input type="radio"/> 3.11 <input type="radio"/> 3.09

<p>> <i>diskw</i> <i>filew</i> 3.09</p>	<p>Replace or Create a File</p> <div style="border: 1px solid black; padding: 5px; margin: 5px 0;"> <p>▶▶---+-->-----+--string--▶◀ +--DISKW--+ +--FILEW--+</p> </div> <ul style="list-style-type: none"> • delegates to diskw.
<p>>> <i>diska</i> <i>filea</i> 3.09</p>	<p>Append to or Create a File</p> <div style="border: 1px solid black; padding: 5px; margin: 5px 0;"> <p>▶▶---+-->>-----+--string--▶◀ +--DISKA--+ +--FILEA--+</p> </div> <ul style="list-style-type: none"> • delegates to diska.
<p>>><i>mdsk</i></p>	<p>Append to or Create a CMS File on a Mode</p> <ul style="list-style-type: none"> • Not implemented in Netrex Pipelines.
<p>>><i>mvs</i></p>	<p>Append to a Physical Sequential Data Set</p> <ul style="list-style-type: none"> • Not implemented in Netrex Pipelines.
<p>>><i>oe</i></p>	<p>Append to or Create an OpenExtensions Text File</p> <ul style="list-style-type: none"> • Not implemented in Netrex Pipelines.
<p>>><i>sfs</i></p>	<p>Append to or Create an SFS File</p> <ul style="list-style-type: none"> • Not implemented in Netrex Pipelines.
<p>>><i>sfsslow</i></p>	<p>Append to or Create an SFS File</p> <ul style="list-style-type: none"> • Not implemented in Netrex Pipelines.

<i>>mnsk</i>	Replace or Create a CMS File on a Mode <ul style="list-style-type: none"> • Not implemented in Netrexx Pipelines.
<i>>mvs</i>	Rewrite a Physical Sequential Data Set or a Member of a Partitioned Data Set <ul style="list-style-type: none"> • Not implemented in Netrexx Pipelines.
<i>>oe</i>	Replace or Create an OpenExtensions Text File <ul style="list-style-type: none"> • Not implemented in Netrexx Pipelines.
<i>>sfs</i>	Replace or Create an SFS File <ul style="list-style-type: none"> • Not implemented in Netrexx Pipelines.
<i><</i> <i>diskr</i> <i>filer</i> <i>3.09</i>	Read a File <div data-bbox="280 589 715 703" style="border: 1px solid black; padding: 5px; margin: 10px 0;"> <pre> ▶---+---<-----+---string---◀ +---DISKR---+ +---FILER---+ </pre> </div> <ul style="list-style-type: none"> • Implemented as in CMS; delegates to diskr.
<i><mnsk</i>	Read a CMS File from a Mode <ul style="list-style-type: none"> • Not implemented in Netrexx Pipelines.
<i><mys</i>	Read a Physical Sequential Data Set or a Member of a Partitioned Data Set <ul style="list-style-type: none"> • Not implemented in Netrexx Pipelines.
<i><oe</i>	Read an OpenExtensions Text File <ul style="list-style-type: none"> • Not implemented in Netrexx Pipelines.
<i><sfs</i>	Read an SFS File <ul style="list-style-type: none"> • Not implemented in Netrexx Pipelines.
<i><sfsslow</i>	Read an SFS File <ul style="list-style-type: none"> • Not implemented in Netrexx Pipelines.
<i>--</i> <i>comment</i> <i>3.09</i>	Comment Stage, No Operation <div data-bbox="280 1487 852 1574" style="border: 1px solid black; padding: 5px; margin: 10px 0;"> <pre> -NetRexx ▶---+ -- ----+---+-----+-----▶ +-COMMENT-+ +-string-+ </pre> </div> <ul style="list-style-type: none"> • delegates to comment. • Not in CMS Pipelines; • This is a STAGE, not a programming comment. It must have a SPACE after --. • It must have either a stageEnd or pipeEnd. • If used before a driver stage, it must have a pipeEnd.
<i>3277bfra</i>	Convert a 3270 Buffer Address Between Representations <ul style="list-style-type: none"> • Not implemented in Netrexx Pipelines.
<i>3277enc</i>	Write the 3277 6-bit Encoding Vector <ul style="list-style-type: none"> • Not implemented in Netrexx Pipelines.

Select Lines Containing Strings (or Not)

```

▶▶--ALL--v-----+-----+---| expression |---▶▶
      +--%debug--+ (6)
      +--%dump--+ (7)
      +--%see----+ (8)
  
```

Notes:

- (1) "expression" consists of one or more delimited strings separated by logical ANDs, ORs, and NOTs, and grouped, if needed, by parentheses.
- (2) "&" is used for AND.
- (3) Since "|" is the default stage separator, "|" may be used for OR.
- (4) Since NetRexx uses "(" and ")" for options -- which are not used in the ALL stage -- "[" and "]" must be used for parentheses.
- (5) CMS Pipelines, having originated on 3270 terminals, uses "~" for NOT. This symbol is not readily typed on terminals running NetRexx Pipelines, so as alternatives, "\", used by NetRexx, (it needs to be doubled to "escape" it) or "^", used by KEX, NOT symbols may be used as alternatives.
- (6) %debug (must be lowercase) NetRexx Pipelines writes the logic line to the file ALL.DEBUG in the current directory. Windows may make it all.debug . CMS Pipelines writes the constructed pipeline (of LOCATE and NLOCATE stages) to ALL DEBUG A.
- (7) %dump (must be lowercase) - writes to the primary output stream as the first record. NetRexx Pipelines writes the logic line. CMS Pipelines writes constructed pipeline.
- (8) %see (must be lowercase) - NetRexx Pipelines Only. Writes the logic line to the standard output (terminal).
- CMS Pipelines uses its own logic order. NetRexx Pipelines uses regular NetRexx logic.

Examples:

```

• literal NetRexx is Good,NetRexx is Great,NetRexx is Fantastic |
  split , |
  all /a/ |
  cons
  
```

```

▶▶NetRexx is Great
▶▶NetRexx is Fantastic
  
```

```

• literal NetRexx is Good,NetRexx is Great,NetRexx is Fantastic |
  split , |
  all / G/ & [/oo/ ! /F/] |
  cons
  
```

```

▶▶NetRexx is Good
  
```

```

• literal NetRexx is Good,NetRexx is Great,NetRexx is Fantastic |
  split , |
  all /R/ & [/oo/ ! /F/] |
  cons
  
```

```

▶▶NetRexx is Good
▶▶NetRexx is Fantastic
  
```

Change the contents of records, from one character to another

```

NetRexx
      +--,--+
      +-----+-----+-----+-----+-----+-----+
      | +-FROM-+          +-TO-+          |
▶▶--ALTER--v-----+-----+-----+-----+-----+-----+
                        +-decimal-+          +-decimal-+
                        +-Hhex-----+          +-Hhex-----+
                        +-Xhex-----+          +-Xhex-----+
  
```


- An variation on the theme of Xedit's ALTER.
- There are pairs of char1s and char2s, optionally separated by commas.
- For each pair of char1 and char2, this changes ALL char1s to char2, like Xedit's 4th and 5th parameters were 1 and 1.
- The chars can be single characters, 2 or 3 digit decimal numerical representations, or beginning with H, h, X, or x hexadecimal representations.
- Also see [TRANSLATE / XLATE](#).
- Not in CMS Pipelines.

<i>alserv</i>	Manage the Virtual Machine's Access List <ul style="list-style-type: none"> • Not implemented in Netrexx Pipelines.
<i>apldecode</i>	Process Graphic Escape Sequences, Old APL language <ul style="list-style-type: none"> • Not implemented in Netrexx Pipelines.
<i>aplencode</i>	Generate Graphic Escape Sequences, Old APL language <ul style="list-style-type: none"> • Not implemented in Netrexx Pipelines.
<i>append</i>	Put Output from a Device Driver after Data on the Primary Input Stream <div style="border: 1px solid black; padding: 5px; margin: 10px 0;"> ▶▶--APPEND--<i>string</i>-----▶◀ </div>
<i>array</i>	Read or Write an Array <ul style="list-style-type: none"> • Pipes for NetRexx
<i>arraya</i>	Read or Write an Array <ul style="list-style-type: none"> • Pipes for NetRexx
<i>arrayr</i>	Read or Write an Array <ul style="list-style-type: none"> • Pipes for NetRexx
<i>arrayw</i>	Read or Write an Array <ul style="list-style-type: none"> • Pipes for NetRexx
<i>asatomc</i>	Convert ASA Carriage Control to CCW Operation Codes. Old printer control <ul style="list-style-type: none"> • Not implemented in Netrexx Pipelines.
<i>asmcont</i>	Join Multiline Assembler Statements <ul style="list-style-type: none"> • Not implemented in Netrexx Pipelines.
<i>asmfind</i>	Select Statements from an Assembler File as XEDIT Find <ul style="list-style-type: none"> • Not implemented in Netrexx Pipelines.
<i>asmnfind</i>	Select Statements from an Assembler File as XEDIT NFind <ul style="list-style-type: none"> • Not implemented in Netrexx Pipelines.
<i>asmxpnd</i>	Expand Joined Assembler Statements <ul style="list-style-type: none"> • Not implemented in Netrexx Pipelines.
<i>beat</i>	Mark when Records Do not Arrive within Interval <ul style="list-style-type: none"> • Not implemented in Netrexx Pipelines.

<p><i>between</i> 3.09</p>	<p>Select Records Between Labels</p> <pre> ▶--BETWEEN-- case +-delimitedString1-+-number-----+--▶ +-Xhexstring1-----+ +-delimitedString2-+ +-Hhexstring1-----+ +-Xhexstring2-----+ +-Bbinstring1-----+ +-Hhexstring2-----+ +-Bbinstring2-----+ case: -----+-- +-ANYcase-----+ +-CASEANY-----+ +-CASEIGNORE--++ +-IGNORECASE--++ +-CASELESS-----+ </pre>
<p><i>bfs</i> <i>hfs</i></p>	<p>Read or Append File in the Hierarchical File System</p> <ul style="list-style-type: none"> • Not implemented in Netrexx Pipelines.
<p><i>bfsdirectory</i> <i>bfsdir</i> <i>hfsdirectory</i> <i>hfsdir</i></p>	<p>Read Contents of a Directory in a Hierarchical File System</p> <ul style="list-style-type: none"> • Not implemented in Netrexx Pipelines.
<p><i>bfsquery</i> <i>bfsq</i> <i>hfsquery</i> <i>hfsq</i></p>	<p>Write Information Obtained from OpenExtensions into the Pipeline</p> <ul style="list-style-type: none"> • Not implemented in Netrexx Pipelines.
<p><i>bfsreplace</i> <i>bfsrep</i> <i>hfsreplace</i> <i>hfsrep</i></p>	<p>Replace the Contents of a File in the Hierarchical File System</p> <ul style="list-style-type: none"> • Not implemented in Netrexx Pipelines.
<p><i>bfsstate</i> <i>bfsstat</i> <i>hfsstate</i> <i>hfsstat</i></p>	<p>Obtain Information about Files in the Hierarchical File System</p> <ul style="list-style-type: none"> • Not implemented in Netrexx Pipelines.
<p><i>bfsxecute</i> <i>bfsx</i> <i>hfsxecute</i> <i>hfsx</i></p>	<p>Issue OpenExtensions Requests</p> <ul style="list-style-type: none"> • Not implemented in Netrexx Pipelines.
<p><i>block</i></p>	<p>Block to an External Format</p> <ul style="list-style-type: none"> • Not implemented in Netrexx Pipelines.
<p><i>browse</i> <i>brw</i></p>	<p>Display Data on a 3270 Terminal</p> <ul style="list-style-type: none"> • Not implemented in Netrexx Pipelines.
<p><i>buffer</i></p>	<p>Buffer Records</p> <pre> ▶--BUFFER--+-----+-----+-----+-----+-----▶ +-number-+-----+--+ +-delimitedString-+ </pre>
<p><i>c14to38</i></p>	<p>Combine Overstruck Characters to Single Code Point. Old printer.</p>
<p><i>casei</i></p>	<p>Run Selection Stage in Case Insensitive Manner</p> <pre> ▶--CASEI--+-----+-----+-----+-----+-----▶ +-ZONE-- inputRange -(1) +-REVERSE-(1) ▶--stage-+-----+-----▶ +-string-+ </pre> <ul style="list-style-type: none"> • (1) CMS Pipelines only.

collate
3.11


Collate Streams



- Not implemented in Netrexx Pipelines.
- (1) NetRexx Pipelines only.
- (2) delimitedString record is put before each Master Record (or after if DETAIL MASTER order) on the primary output stream.
- 3.11 New to NetRexx Pipelines. Add SEPARATOR option.

combine


Combine Data from a Run of Records



- (1) Only for use with secondary input streams. Only options from this column usable with any secondary input streams. (This is poorly documented in CMS Pipelines. This is a best guess of their intentions.)
- (2) Not usable with STOP and secondary streams.

command
cmd

Issue OS Commands, Write Response to Pipeline



- input stream 0 is for commands
- input stream 1 is stdin
- output stream 0 is stdout
- output stream 1 is the return code
- output stream 2 is stderr

comment
--
3.09

Comment stage

```
NetRexx
▶---+---COMMENT---+---+-----+---▶
      +  --  -----+  +---string---+
```

- Not in CMS Pipelines;
- This is a STAGE, not a programming comment. It must have a SPACE after --.
- It must have either a stageEnd or pipeEnd.
- If ended with a stageEnd, it passes records through on primary input to output streams.
- If ended with a pipeEnd, it does NOT pass records through.
- If used before a driver stage, it must have a pipeEnd.

compare

Compare Primary and Secondary Streams, Write the Result

```
NetRexx
      +-TRINARY--+ (1)                +-PAD SPACE--+
▶---COMPARE---+-----+-----+-----+-----+-----+-----+-----▶
      +-BINARY--+ (2)                +-PAD-xorc--+ +-ECHO--+
      |                               |
      |-----+
      +-ANY delimitedString-----+ (4) (5)
      +-EQUAL delimitedString-----+ (4)
      +-LESS delimitedString-----+ (3) (4)
      +-MORE delimitedString-----+ (3) (4)
      +-NOTEQUAL delimitedString--+ (4)
```

- (1) -1 = Primary is shorter/less, 0 = equal, 1 = Secondary is shorter/less
- (2) 0 = equal, 1 = not equal
- (3) Primary is LESS/shorter (or MORE/longer) than secondary
- (4) *DStrings* can use any of the following escapes (or the lowercase) for the unequal situation:
 - \C (count) for the record number,
 - \B (byte) for column number
 - \P (primary) for the primary stream record
 - \S (secondary) for the secondary stream record
 - \L (Least) for the stream number that is shorter, -1 if equal
 - \M (Most) for the stream number that is longer, -1 if equal
- (5) Equal or not, this *DString* precedes any of the others.
- (6) This is NetRexx Pipelines only, not included in CMS
- (7) In reporting \P & \S, control characters, except new line, \n, are transliterated to [blob, 219.d2c()]
- (8) Without ECHO, this stops and reports at first non-compare. With ECHO, each primary input is reported; after first non-compare primary input stream records continue to be read and reported, but no testing is done.
- (9) Options work in any order
- Input streams:
 - 0: Data 1
 - 1: Data 2
- Output streams:
 - 0: Result (single record, possibly multiple lines)
 - 1: Last primary record read at first no match, or end of stream
 - 2: Last secondary record read at first no match, or end of stream

configure

Set and Query CMS Pipelines Configuration Variables

- Not implemented in Netrex Pipelines.


```

▶--DATECONVert--+-+-----+-----▶
                    +--inputRange- (3) -+

+--SHOrtdate ISOdate-----+ +--WINDOW -50-----+
▶+-----+-----+-----+-----▶
|                               +-ISOrtdate-----+ +-WINDOW-signednumber-+
+-| Inputformat |+-+-----+-----+ +-BASEYEAR-yearnumber-+
|   +-PREFACE-+ | +-| Outputformat |+-+
+-NOW-- (5) -----+
                    +-APPEND--+

                    +-MIDNIGHT-- (4) -+
▶+-----+-----+-----+-----▶
                    +--TIMEOUT--+ +--NOON-- (4) -----+

```

Inputformat,	Outputformat:
SHOrtdate } USA_SHORT } REXX_DATE_U }	mm/dd/yy hh:mm:ss.uuuuuu
FULldate } USA }	mm/dd/yyyyyy hh:mm:ss.uuuuuu
ISO_SHORT ISOdate DB2_SHORT DB2	yy-mm-dd hh:mm:ss.uuuuuu yyyyyy-mm-dd hh:mm:ss.uuuuuu yy-mm-dd-hh.mm.ss.uuuuuu yyyyyy-mm-dd-hh.mm.ss.uuuuuu
VMDATE (2) NORMAL CSL_SHORT } REXX_DATE_O }	dd mmm yyyyyyy hh:mm:ss.uuuuuu yy/mm/dd hh:mm:ss.uuuuuu
CSL PIPE_SHORT PIPE } REXX_DATE_S }	yyyyyy/mm/dd hh:mm:ss.uuuuuu yymmddhmmssuuuuuu yymmddhmmssuuuuuu
EURSHORT EUR JULIAN_SHORT JULIAN	dd.mm.yy hh:mm:ss.uuuuuu dd.mm.yyyyyyy hh:mm:ss.uuuuuu yy.ddd hh:mm:ss.uuuuuu yyyyyy.ddd hh:mm:ss.uuuuuu
TOD ABSOLUTE } (2) TODABS } (2) SCIENTIFIC_ABSOLUTE } (2) SCIABS } (2) POSIX TOD RELATIVE } (2) TODREL } (2) SCIENTIFIC_RELATIVE } (2) SCIREL } (2) MET (2)	ssssssss

The following can be REXX_DATE_x, REXXx, or Rx

REXX_DATE_B (2)	
REXX_DATE_C (2)	
REXX_DATE_D	ddd hh:mm:ss.uuuuuu
REXX_DATE_E	dd/mm/yy hh:mm:ss.uuuuuu
REXX_DATE_E_LONG	dd/mm/yyyyyy hh:mm:ss.uuuuuu
REXX_DATE_J	yyddd hh:mm:ss.uuuuuu
REXX_DATE_J_LONG	yyyyddd hh:mm:ss.uuuuuu
REXX_DATE_M	mmmmmmmmmm (output only)
REXX_DATE_N_SHORT	dd mmm yy hh:mm:ss.uuuuuu
REXX_DATE_N	dd mmm yyyy hh:mm:ss.uuuuuu
REXX_DATE_W	wwwwwwww (output only)

- (1): SPACE is optional here.
- (2) Not implemented in NetRexx Pipelines at this time; mainly mainframe useful only.
- (3): NetRexx Pipelines uses IRange which gives a superset of range options.
- (4): NetRexx Pipelines only. What time to assume if blank time on input.
- (5): NetRexx Pipelines only.
 - Use current local date time.
 - Any Inputrange is ignored.
 - Any output format can be used.
 - PREFACE Write the date record before passing the input to the output.

- APPEND Write the output record after passing the input to the output.
- Bad date records out on secondary. Or error if not connected.

deal

NetRexx Pipelines is more forgiving on input format:

Pass Input Records to Output Streams Round Robin

- LONG, SHORT, and normal can all read either 2- or 4-digit years and process per the format;
- leading zeros/blanks can be ignored except where there is no punctuation.

```

+-STOP--ALLEOF-----+
▶▶--DEAL--+-----▶▶
+-STOP--+--ALLEOF- (2) +-----+
|         +-ANYEOF----+         |
|         +-number----+         |
+-SECONDARY--+-----+
|         +-RELEASE----+         |
|         +-LATCH- (1) -+         |
+-KEY--inputRange--+-----+
|         +-STRIP-+         |
+-STREAMid--inputRange--+-----+
|         +-STRIP-+         |

```

- (1) Not yet in NetRexx Pipelines
- (2) Not CMS
- Since Java dispatches the stage threads, DEAL may not see a sever immediately, as the severing thread can get multitasked. This can make options like 'ANYEOF' work in unexpected ways.

deblock

Deblock External Data Formats

```

+-80-----+
+--FIXED--+number+-----+
|         +-PAD--xorc--+ (1)         |
▶▶--DEBLOCK--+-----▶▶
+--C-----+-----+-----+
+-J-----+ +-TERMINATE-+ +-EOF-+
+-CRLF-----+
+-LINEND xorc-----+
+-STRING--delimitedString-+

```

- CMS has many more mainframe centric formats that NetRexx Pipelines does not process.
- (1) Not CMS Pipelines

decode64
64decode
3.11

Decode Base-64 Format

```

+-MIME--+
▶▶--+DECODE64--+-----▶▶
+-64DECODE-+ +-BASIC-+
+-URL-----+

```

- NOTE: CMS is only 64DECODE, and does not have the options; it does MIME.
- BASIC - Output is mapped to a set of characters lying in A-Za-z0-9+/. The encoder does not add any line feed in output, and the decoder rejects any character other than A-Za-z0-9+/.
- URL - Output is mapped to set of characters lying in A-Za-z0-9+_. Output is URL and filename safe.
- MIME - Output is mapped to MIME friendly format. Output is represented in lines of no more than 76 characters each, and uses a carriage return 'r' followed by a linefeed 'n' as the line separator. No line separator is present to the end of the encoded output.
- 3.11: New to NetRexx. Add MIME, BASIC, & URL options.

<i>digest</i>	<p>Compute a Message Digest</p> <pre> ▶--DIGEST--+-SHA1-----+-----▶ +-SHA224-----+ +-APPEND- (1) -----+ +-SHA256-----+ +-VERIFY- (1) -----+ +-SHA384-----+ +---NOT- (1) --+ +-SHA512-----+ +-MD5-----+ +-MD2- (2) -----+ +-SHA512/224- (2) --+ +-SHA512/256- (2) --+ </pre> <p>(1) CMS Pipelines only. (2) NetRexx Pipelines only (dependent on the JVM implementation).</p> <p>NetRexx Pipelines returns the bytearray as a HEX string CMS returns a char array into the pipeline</p>
<i>disk file</i>	<p>Read a File</p> <pre> ▶--+-DISK--+-string--▶ +---FILE---+ </pre> <ul style="list-style-type: none"> As in CMS, equivalent to diskr (Pipes for NetRexx Only) or <.
<i>diska filea >></i>	<p>Append to or Create a File</p> <pre> ▶--+-DISKA--+-string--▶ +---FILEA---+ +--->>-----+ </pre>
<i>diskback fileback</i>	<p>Read a File Backwards</p> <ul style="list-style-type: none"> Not implemented in Netrex Pipelines.
<i>diskfast filefast</i>	<p>Read, Create, or Append to a File</p> <ul style="list-style-type: none"> Not implemented in Netrex Pipelines.
<i>diskid</i>	<p>Map CMS Reserved Minidisk</p> <ul style="list-style-type: none"> Not implemented in Netrex Pipelines.
<i>diskr filer <</i>	<p>Read a File</p> <pre> ▶--+-DISKR--+-string--▶ +---FILER---+ +---<-----+ </pre> <ul style="list-style-type: none"> As in CMS, equivalent to diskr (Pipes for NetRexx Only) or <.
<i>diskrandom filerandom</i>	<p>Random Access a File</p> <ul style="list-style-type: none"> Not implemented in Netrex Pipelines.
<i>diskslow fileslow</i>	<p>Read, Create, or Append to a File</p> <pre> ▶--+-DISKSLOW--+-string--▶ +---FILESLOW--+ </pre>
<i>diskupdate fileupdate</i>	<p>Replace Records in a File</p> <ul style="list-style-type: none"> Not implemented in Netrex Pipelines.
<i>diskw filew ></i>	<p>Replace or Create a File</p> <pre> ▶--+-DISKW--+-string--▶ +---FILEW---+ +--->-----+ </pre>

<p><i>drop</i></p>	<p>Discard Records from the Beginning or the End of the File</p> <div data-bbox="279 129 1141 273" style="border: 1px solid black; padding: 5px; margin: 10px 0;"> <pre> +-FIRST-+ +-1-----+ ▶▶--DROP--+-----+-----+-----+-----▶▶ +-LAST--+ +-snumber- (1)+ +-BYTES-+ +-*-----+ </pre> </div> <ul style="list-style-type: none"> (1) CMS: must be positive. NetRexx Pipelines: negative reverses FIRST/LAST, so DROP FIRST -3 is the same as DROP LAST 3.
<p><i>duplicate</i> <i>duplicat</i> <i>duplica</i> <i>duplic</i> <i>dupli</i> <i>dupl</i> <i>dup</i></p>	<p>Copy Records</p> <div data-bbox="279 436 901 609" style="border: 1px solid black; padding: 5px; margin: 10px 0;"> <pre> +-1-----+ ▶▶--DUPLICATE- (1) -+-----+-----▶▶ +-number-+ +-*-----+ +- -1-----+ </pre> </div> <ul style="list-style-type: none"> (1) CMS is DUPlicat due to 8-character name limitation
<p><i>elastic</i></p>	<p>Buffer Sufficient Records to Prevent Stall</p> <div data-bbox="279 743 654 801" style="border: 1px solid black; padding: 5px; margin: 10px 0;"> <pre> ▶▶--ELASTIC-----▶▶ </pre> </div>
<p><i>encode64</i> <i>64encode</i> <i>3.11</i></p>	<p>Encode to Base-64 Format</p> <p>NetRexx</p> <div data-bbox="279 862 778 1003" style="border: 1px solid black; padding: 5px; margin: 10px 0;"> <pre> +-MIME--+ ▶▶--+-64ENCODE-+--+-----+-----▶▶ +-ENCODE64-+ +-BASIC-+ +-URL----+ </pre> </div> <ul style="list-style-type: none"> NOTE: CMS is only 64DECODE, and does not have the options; it does MIME. BASIC - Output is mapped to a set of characters lying in A-Za-z0-9+/. The encoder does not add any line feed in output, and the decoder rejects any character other than A-Za-z0-9+/. URL - Output is mapped to set of characters lying in A-Za-z0-9+_. Output is URL and filename safe. MIME - Output is mapped to MIME friendly format. Output is represented in lines of no more than 76 characters each, and uses a carriage return '\r' followed by a linefeed '\n' as the line separator. No line separator is present to the end of the encoded output. 3.11: New to NetRexx. Add MIME, BASIC, & URL options.
<p><i>eofback</i></p>	<p>Run an Output Device Driver and Propagate End-of-File Backwards</p> <ul style="list-style-type: none"> Not implemented in Netrex Pipelines.
<p><i>escape</i></p>	<p>Insert Escape Characters in the Record</p> <ul style="list-style-type: none"> Not implemented in Netrex Pipelines.
<p><i>fanin</i></p>	<p>Concatenate Streams</p> <div data-bbox="279 1572 837 1684" style="border: 1px solid black; padding: 5px; margin: 10px 0;"> <pre> ▶▶--FANIN--+-----+-----▶▶ -----+ +---stream-++ </pre> </div>
<p><i>faninany</i></p>	<p>Copy Records from Whichever Input Stream Has One</p> <div data-bbox="279 1814 821 1899" style="border: 1px solid black; padding: 5px; margin: 10px 0;"> <pre> ▶▶--FANINANY--+-----+-----▶▶ +---STRICT- (1) ---+ </pre> </div> <ul style="list-style-type: none"> (1) CMS only.
<p><i>fanintwo</i></p>	<p>Pass Records to Primary Output Stream</p>

<i>fanout</i>	Copy Records from the Primary Input Stream to All Output Streams <div style="border: 1px solid black; padding: 5px; margin: 5px 0;"> <pre> +-STOP--ALLEOF-----+ ▶--FANOUT--+-----+-----▶ +-STOP--+-ANYEOF-----+ +-ALLOF-- (1) ----+ +-number-----+ </pre> </div> <ul style="list-style-type: none"> • (1) CMS only
<i>fanouttwo</i>	Copy Records from the Primary Input Stream to Both Output Streams
<i>fbaread</i>	Read Blocks from a Fixed Block Architecture Drive <ul style="list-style-type: none"> • Not implemented in Netrexx Pipelines.
<i>fbawrite</i>	Write Blocks to a Fixed Block Architecture Drive <ul style="list-style-type: none"> • Not implemented in Netrexx Pipelines.
<i>fblock</i>	Block Data, Spanning Input Records <div style="border: 1px solid black; padding: 5px; margin: 5px 0;"> <pre> ▶--FBLOCK--number--+-----+-----▶ +-xorc--+ </pre> </div>
<i>file disk</i>	Read or Write a File <div style="border: 1px solid black; padding: 5px; margin: 5px 0;"> <pre> ▶--+-FILE--+-string--▶ +-DISK--+ </pre> </div>
<i>filea diska >></i>	Append to or Create a File <div style="border: 1px solid black; padding: 5px; margin: 5px 0;"> <pre> ▶--+-FILEA--+-string--▶ +-DISKA--+ +-->>-----+ </pre> </div>
<i>fileback diskback</i>	Read a CMS file backwards <ul style="list-style-type: none"> • Not implemented in Netrexx Pipelines.
<i>filedescriptor</i>	Read or Write an OpenExtensions File that Is Already Open <ul style="list-style-type: none"> • Not implemented in Netrexx Pipelines.
<i>filefast diskfast</i>	Read or write a CMS file <ul style="list-style-type: none"> • Not implemented in Netrexx Pipelines.
<i>filer file disk diskr <</i>	Read a File <div style="border: 1px solid black; padding: 5px; margin: 5px 0;"> <pre> ▶--+-FILER--+-string--▶ +-DISKR--+ +--<-----+ </pre> </div>
<i>filerandom diskrandom</i>	Read specific records from a CMS file
<i>fileslow diskslow</i>	Read, Create, or Append to a File <div style="border: 1px solid black; padding: 5px; margin: 5px 0;"> <pre> ▶--+-FILESLOW--+-string--▶ +-DISKSLow--+ </pre> </div>
<i>filetoken</i>	Read or Write an SFS File That is Already Open <ul style="list-style-type: none"> • Not implemented in Netrexx Pipelines.
<i>fileupdate diskupdate</i>	Change records in a CMS file

<i>filew diskw ></i>	Replace or Create a File <div style="border: 1px solid black; padding: 5px; margin: 5px 0;"> ▶▶---+---FILEW---+---string---◀◀ +---DISKW---+ +--->-----+ </div>
<i>fillup</i>	Pass Records To Output Streams <ul style="list-style-type: none"> • Not implemented in Netrexx Pipelines.
<i>filterpack</i>	Manage Filter Packages <ul style="list-style-type: none"> • Not implemented in Netrexx Pipelines.
<i>find</i>	Select Lines by XEDIT Find Logic <div style="border: 1px solid black; padding: 5px; margin: 5px 0;"> ▶▶-----FIND---+-----+-----◀◀ +---string---+ </div>
<i>fitting</i>	Source or Sink for Copipe Data <ul style="list-style-type: none"> • Not implemented in Netrexx Pipelines.
<i>fmtfst</i>	Format a File Status Table (FST) Entry <ul style="list-style-type: none"> • Not implemented in Netrexx Pipelines.
<i>fmlabel fromlabel</i>	Select Records from the First One with Leading String <div style="border: 1px solid black; padding: 5px; margin: 5px 0;"> ▶▶-----FRLABEL---+-----+-----◀◀ +---string---+ </div>
<i>fromlabel fmlabel</i>	Select Records from the First One with Leading String <div style="border: 1px solid black; padding: 5px; margin: 5px 0;"> ▶▶-----FROMLABEL---+-----+-----◀◀ +---string---+ </div>
<i>frtarget</i>	Select Records from the First One Selected by Argument Stage <div style="border: 1px solid black; padding: 5px; margin: 5px 0;"> ▶▶---+---FRTARGET---+---stage---+-----+-----◀◀ +---FROMTARGet---+ +---operands---+ </div>
<i>fullscreen fullscree fullscre fullscr</i>	Full screen 3270 Write and Read to the Console or Dialed/Attached Screen <ul style="list-style-type: none"> • Not implemented in Netrexx Pipelines.
<i>fullscrq</i>	Write 3270 Device Characteristics <ul style="list-style-type: none"> • Not implemented in Netrexx Pipelines.
<i>fullscrq</i>	Write 3270 Device Characteristics <ul style="list-style-type: none"> • Not implemented in Netrexx Pipelines.
<i>fullscrs</i>	Format 3270 Device Characteristics <ul style="list-style-type: none"> • Not implemented in Netrexx Pipelines.
<i>gate</i>	Pass Records Until Stopped <div style="border: 1px solid black; padding: 5px; margin: 5px 0;"> ▶▶---GATE---+-----+-----◀◀ +---STRICT---+ </div>
<i>gather</i>	Copy Records From Input Streams <ul style="list-style-type: none"> • Not implemented in Netrexx Pipelines.


<p><i>gen</i></p>	<p>Generate a Sequence of Numbers Starting with 1</p> <pre>NetRexx ▶▶--GEN--number-----▶▶</pre> <ul style="list-style-type: none"> • Not implemented in CMS Pipelines.
<p><i>getfiles</i> <i>getfiles</i> <i>getfile</i> <i>getfil</i> <i>getfi</i> <i>getf</i> <i>get</i></p>	<p>Read Files</p> <pre>▶▶--GETfiles-----▶▶</pre>
<p><i>getovers</i></p>	<p>Write the Contents of Objects</p> <pre>NetRexx ▶▶--GETOVERS-----▶▶</pre> <ul style="list-style-type: none"> • Input stream 0 should contain rexx objects. The getovers stage will output the index and contents of the stem on stream 0. If output stream 1 is connected, the root is placed there. Any severed streams will cause then stage to exit. Passing a non rexx object will cause the stage to exit with return code 13. • Pipes for NetRexx only.
<p><i>getstems</i></p>	<p>Write the Contents of Members of Stems</p> <pre>NetRexx ▶▶--GETSTEMS-----▶▶</pre> <ul style="list-style-type: none"> • Input stream 0 should contain rexx objects containing stems. The getstems stage will output the contents of the stem on stream 0. If output stream 1 is connected, the root is placed there. Any severed streams will cause then stage to exit. Passing a non rexx stem object will cause the stage to exit with return code 13. • Pipes for NetRexx only.
<p><i>grep</i> <i>regex</i> 3.09</p>	<p>Select Lines by a Regular Expression</p> <pre>NetRexx ▶▶--+-GREP-+-+-----+-regex_Dstring-(1)---▶▶ +--REGEX--+ +-(-- options_string --)-+ options_string: -----+ --+-----+-----+-----+-----+ +-Numbers-----+ (2) +-Before+-1-----+ (3) +-number-+ +-After+-1-----+ (3) +-number-+ +-Context+-1-----+ (4) +-number-+ +-NOseparator-----+ (5) +-Separator+--/--/--+ (5) +-delimitedString-+ +-Tertiary-----+ (6) +-COUnt-----+ (7)</pre> <ul style="list-style-type: none"> • NetRexx Pipelines only. • Records matching the RegEx are put out on primary output. • Records not matching are put out on secondary, if connected, or discarded. • . • (1) Regex_string is a Java RegEx expression. Null string passes all records. • (2) Records are prefaced with records number, 10 characters, right justified. • (3) Number of records put out after a matching record. • (4) Number of records put out before and after a matching record. • (5) Inserted before a group of "before records" or the found record with "after records." • (6) Send all matching records (no numbers) to tertiary output stream, if connected. • (7) Only a count of matches is put out on the primary output stream. (Other options probably should not be used with this.)

<p><i>hash dict</i></p>	<p>Read or Write a Dictionary</p> <pre>NetRexx ▶---+HASH+---name---▶ +-DICT-+</pre> <ul style="list-style-type: none"> • Pipes for NetRexx only.
<p><i>hasha dicta</i></p>	<p>Write a Dictionary</p> <pre>NetRexx ▶---+HASHA+---name---▶ +-DICTA-+</pre> <ul style="list-style-type: none"> • Pipes for NetRexx only.
<p><i>hashr dictr</i></p>	<p>Read a Dictionary</p> <pre>NetRexx ▶---+HASHR+---name---▶ +-DICTR-+</pre> <ul style="list-style-type: none"> • Pipes for NetRexx only.
<p><i>hashw dictw</i></p>	<p>Write a Dictionary</p> <pre>NetRexx ▶---+HASHW+---name---▶ +-DICTW-+</pre> <ul style="list-style-type: none"> • Pipes for NetRexx only.
<p><i>help ahelp ?</i></p>	<p>Display Help for Pipelines</p> <pre>▶---+HELP+-----+-----▶ +-AHELP--+ +-word-----+ +-?- (3) ---+ +BUILTINS- (1) ---+ +-MENU- (1) -+ +COMMANDS- (1) ---+ +HOST- (1) -----+ +MESSAGES- (1) ---+ +OTHER- (1) -----+ +SYNTAX- (1) -----+ +-MSG- (1) --number-----+ +-number- (1) -----+ +-SQL- (1) --string-----+ +-SQLCODE- (1) --+-----+ +number--+</pre> <p>(1) CMS Pipelines only. Not yet in NetRexx Pipelines. (2) If primary output is connected, lines are propagated, otherwise they are sent to the console by "say." (3) ? is the default pipeEnd character. Here it is useful only when a different pipeEnd is defined.</p>
<p><i>hfs bfs</i></p>	<p>Read or Append File in the Hierarchical File System</p> <ul style="list-style-type: none"> • Not implemented in Netrex Pipelines.
<p><i>hfsdirectory hfdir bfsdirectory bfsdir</i></p>	<p>Read Contents of a Directory in a Hierarchical File System</p> <ul style="list-style-type: none"> • Not implemented in Netrex Pipelines.
<p><i>hfsquery hfsq bfsquery bfsq</i></p>	<p>Write Information Obtained from OpenExtensions into the Pipeline</p> <ul style="list-style-type: none"> • Not implemented in Netrex Pipelines.
<p><i>hfsreplace hfsrep bfsreplace bfsrep</i></p>	<p>Replace the Contents of a File in the Hierarchical File System</p> <ul style="list-style-type: none"> • Not implemented in Netrex Pipelines.

<i>hfsstate</i> <i>hfsstat</i> <i>bfsstate</i> <i>bfsstat</i>	Obtain Information about Files in the Hierarchical File System <ul style="list-style-type: none"> • Not implemented in Netrexx Pipelines.
<i>hfsxecute</i> <i>hfsx</i> <i>bfsxecute</i> <i>bfsx</i>	Issue OpenExtensions Requests <ul style="list-style-type: none"> • Not implemented in Netrexx Pipelines.
<i>hiasm</i>	Interface to High Level Assembler <ul style="list-style-type: none"> • Not implemented in Netrexx Pipelines.
<i>hiasmerr</i>	Extract Assembler Error Messages from the SYSADATA File <ul style="list-style-type: none"> • Not implemented in Netrexx Pipelines.
<i>hole</i>	Destroy Data <div data-bbox="279 593 609 649" style="border: 1px solid black; padding: 5px;"> ▶▶--HOLE-----▶◀ </div>
<i>hostbyaddr</i> 3.09	Resolve IP Address into Domain and Host Name <div data-bbox="279 705 1216 795" style="border: 1px solid black; padding: 5px;"> ▶▶-----HOSTBYADDR -----+-----+-----▶◀ +--INCLUDEIP----+ (1) </div> <ul style="list-style-type: none"> • (1) Optional parameter not present in VM/CMS version • INCLUDEIP - Also include the IP address along with the hostname. Output: <hostname>/<ip address> Example: dns.google/8.8.8.8 • Known issues: The underlying Java method getByName/getHostName does not appear to handle IPv6 addresses in any known and consistent manner. Could be related to a host configuration issue but googling shows odd and inconsistent results for getting around this.
<i>hostbyname</i> 3.09	Resolve a Domain Name into an IP Address <div data-bbox="279 1108 1157 1198" style="border: 1px solid black; padding: 5px;"> ▶▶--HOSTBYNAME -----+-----+-----▶◀ +--INCLUDENAME--+ (1) </div> <ul style="list-style-type: none"> • (1) Optional parameter not present in CMS Pipelines • Arguments: INCLUDENAME - Also include the name of the host on output. • Output: <hostname>/<ip address> Example: dns.google/8.8.8.8
<i>hostid</i> 3.09	Write TCP/IP Default IP Address <div data-bbox="279 1467 1125 1556" style="border: 1px solid black; padding: 5px;"> ▶▶--HOSTID---+-----+-----▶◀ +--USERid--word- (1) --+ </div> <ul style="list-style-type: none"> • (1) The USERid option available under CMS Pipelines is not applicable and is ignored in NetRexx Pipelines
<i>hostname</i> 3.09	Write TCP/IP Host Name <div data-bbox="279 1691 1248 1780" style="border: 1px solid black; padding: 5px;"> ▶▶--HOSTNAME--+-----+-----+-----▶◀ +--INCLUDEIP-- (1) -+ +--USERid--word- (2) --+ </div> <ul style="list-style-type: none"> • (1) Optional parameter not present in VM/CMS version • (2) The USERid option available under CMS is not applicable and is ignored in NetRexx Pipelines • Arguments: INCLUDEIP - include the IP address of the system in the response in the form <hostname>/<ip address>

htmlrows
htmlrow
3.11

Convert rows to HTML format



- HTMLROWS reads rows from its primary input stream and writes them to its primary output stream, altering them to have the proper HTML tags for TABLE ROWS.
- I.e., it converts
abc,mnop,xyz
into
<tr><td>abc</td><td>mnop</td><td>xyz</td></tr>
- The SEPARATOR QString, by default the comma character, can be specified.
- There are options to put additional data inside the tags. This could be used for class or style tag options, for example.
 - ROW QString : puts its information into the <tr>-tags
 - DATA QString : puts its information into the <td>-tags
 - HEAD QString : puts its information into the <th>-tags (1)
- QString is a quoted string of characters. The quote marks may be either single or double, but must match. If there are no spaces in the string, the quote marks are optional.
- (1) If there is a HEAD option, the first row read has <th>-tags instead of <td>-tags. It must have a QString of at least "". Succeeding rows have the standard <td>-tags.

httpsplit

Split HTTP Data Stream

- Not implemented in Netrexx Pipelines.

iebcopy

Process IEBCOPY Data Format

- Not implemented in Netrexx Pipelines.

if

Process Records Conditionally

- Not implemented in Netrexx Pipelines.


immcmd

Write the Argument String from Immediate Commands

- Not implemented in Netrexx Pipelines.

insert

Insert String in Records



- insert a string into a record before or after the record content. Will be much more efficient than specs especially if the input is a Byte[]

inside

Select Records between Labels



instore

Load the File into a storage Buffer

- Not implemented in Netrexx Pipelines.

ip2socka

Build sockaddr_in Structure

- Not implemented in Netrexx Pipelines.

<i>ispf</i>	Access ISPF Tables <ul style="list-style-type: none"> Not implemented in Netrexx Pipelines.
<i>jeremy</i>	Write Pipeline Status to the Pipeline <ul style="list-style-type: none"> Not implemented in Netrexx Pipelines.
<i>join</i>	Combine Records <pre> +-1-----+ ▶--JOIN-+-----+-----▶ +-COUNT-+ +-number-----+ +-*-----+ +-KEYLENGth--number-+ ▶+-----+-----+-----▶ +-delimitedString-+ +-number-+ +-TERMinate-+ </pre>
<i>joincont</i>	Join Continuation Lines <pre> +-TRAILING-----+ ▶--JOINCONT--+-----+-----▶ +-ANYCase----+ +-NOT-+ +-RANGE--inputRange-+ +-DELAY-+ +-CASEANY----+ +-LEADING-----+ +-CASEIGNORE-+ +-IGNORECASE-+ +-CASELESS---+ ▶+-----+delimitedString-+-----+-----▶ +-ANYof-+ +-KEEP-+ +-delimitedString-+ </pre>
<i>juxtapose</i>	Preface Record with Marker <pre> ▶--JUXTAPOSE-----+-----+-----▶ +-COUNT-+ </pre>
<i>ldrtbls</i>	Resolve a Name from the CMS Loader Tables <ul style="list-style-type: none"> Not implemented in Netrexx Pipelines.
<i>listcat</i>	Obtain Data Set Names <ul style="list-style-type: none"> Not implemented in Netrexx Pipelines.
<i>listdsi</i>	Obtain Information about Data Sets <ul style="list-style-type: none"> Not implemented in Netrexx Pipelines.
<i>listispf</i>	Read Directory of a Partitioned Data Set into the Pipeline <ul style="list-style-type: none"> Not implemented in Netrexx Pipelines.
<i>listpds</i>	Read Directory of a Partitioned Data Set into the Pipeline <ul style="list-style-type: none"> Not implemented in Netrexx Pipelines.
<i>listzip</i>	List the Files in a Zipped File <pre> NetRexx ▶--LISTZIP----zipFileName-----▶ </pre>
<i>literal</i>	Write the Argument String <pre> ▶--LITERAL-----+-----+-----▶ +-string-+ </pre>

locate
locat
loca
loc
lo
l

Select Lines that Contain a String

```
▶--Locate-+-----+-----+-----+-----+-----+-----+-----▶
      +-ANYCase-----+ +-MIXED-(1)-+ +-inputRanges-+ +-ANYof-+
      +-CASEANY-----+ +-ONEs--(1)-+
      +-CASEIGNORE--+ +-ZEROs-(1)-+
      +-IGNORECASE--+
      +-CASELESS-----+

▶+-----+-----+-----+-----+-----+-----+-----▶
      +-delimitedString-
```

- (1) Not in NetRexx Pipelines, yet.
- [2] IBM documentation has this as "LOCATE" rather than "Locate". But the abbreviations work in both systems.

lookup

Find Records in a Reference Using a Key Field

```
NetRexx
▶--LOOKUP-+-----+-----+-----+-----+-----+-----+-----▶
      +-COUNT-+ +-ANYCASE-+ +-AUTOADD-+ +-BEFORE-+

▶+-----+-----+-----+-----+-----+-----+-----▶
      +-KEYONLY-+ +-SETCOUNT-+ +-INCREMENT-+ +-TRACKCOUNT-+

▶-----+-----+-----+-----+-----+-----+-----▶
      +-inputRange-+-----+
      +-inputRange-+

▶+-----+-----+-----+-----+-----+-----+-----▶
      +-DETAIL MASTER-----+
      +-DETAIL ALLMASTER PAIRWISE-+
      +-DETAIL ALLMASTER-----+
      +-DETAIL-----+
      +-MASTER DETAIL-----+
      +-MASTER-----+
      +-ALLMASTER DETAIL PAIRWISE-+
      +-ALLMASTER DETAIL-----+
      +-ALLMASTER-----+
```

- in stream 0 are detail records
- in stream 1 are master records
- in stream 2 adds to masters
- in stream 3 delete from masters
-
- out stream 0 are matched records
- out stream 1 are unmatched detail records
- out stream 2 are unmatched or counted master records
- out stream 3 deleted masters
- out stream 4 duplicate masters
- out stream 5 unmatched master deletes
-
- lookup does not consider an unconnected output stream an error. It does propropagate EOFs from output streams.

lookup

Find Records in a Reference Using a Key Field

```

CMS
▶▶--LOOKUP--+-+-----+-+-----+-+-----+-+-----+-+-----▶
          +-COUNT-+ +-MAXcount-number-+ +-INCREMENT-+

          +-NOPAD-----+
▶+-----+-+-----+-+-----+-+-----+-+-----▶
  +-SETCOUNT-+ +-TRACKCOUnT-+ +-PAD-xorc-+ +-ANYcase-+

▶+-----+-+-----+-+-----+-+-----+-+-----▶
  +-AUTOADD-+-+-----+-+ +-KEYONLY-+ +-STRICT-+
  |           +-BEFORE-+ |
  +-CEILING-----+
  +-FLOOR-----+

▶+-----+-+-----+-+-----▶
  +-inputRange-+-+-----+-+
          +-inputRange-+

  +-DETAIL MASTER-----+
▶+-----+-+-----+-+-----▶
  +-DETAIL ALLMASTER PAIRWISE-+
  +-DETAIL ALLMASTER-----+
  +-DETAIL-----+
  +-MASTER DETAIL-----+
  +-MASTER-----+
  +-ALLMASTER DETAIL PAIRWISE-+
  +-ALLMASTER DETAIL-----+
  +-ALLMASTER-----+

```

- in stream 0 are detail records
- in stream 1 are master records
- in stream 2 adds to masters
- in stream 3 delete from masters
-
- out stream 0 are matched records
- out stream 1 are unmatched detail records
- out stream 2 are unmatched or counted master records
- out stream 3 deleted masters
- out stream 4 duplicate masters
- out stream 5 unmatched master deletes
-
- lookup does not consider an unconnected output stream an error. It does propropagate EOFs from output streams.

maclib

Generate a Macro Library from Stacked Members in a COPY File

- Not implemented in Netrexx Pipelines.

mapmdisk

Map Minidisks Into Data spaces

- Not implemented in Netrexx Pipelines.

mctoasa

Convert CCW Operation Codes to ASA Carriage Control

- Not implemented in Netrexx Pipelines.


<i>mdiskblk</i>	Read or Write Minidisk Blocks <ul style="list-style-type: none"> Not implemented in Netrexx Pipelines.
<i>mdskrandom</i> <i>mdskrand</i>	Random Access a CMS File on a Mode <ul style="list-style-type: none"> Not implemented in Netrexx Pipelines.
<i>mdskslow</i>	Read, Append to, or Create a CMS File on a Mode <ul style="list-style-type: none"> Not implemented in Netrexx Pipelines.
<i>mdskupdate</i> <i>mdskupda</i>	Replace Records in a File on a Mode <ul style="list-style-type: none"> Not implemented in Netrexx Pipelines.
<i>members</i> <i>member</i>	Extract Members from a Partitioned Data Set <ul style="list-style-type: none"> Not implemented in Netrexx Pipelines.
<i>merge</i>	Merge Streams <ul style="list-style-type: none"> Not implemented in Netrexx Pipelines.
<i>mjsc</i>	Issue Commands to a WebSphere MQ Queue Manager <ul style="list-style-type: none"> Not implemented in Netrexx Pipelines.
<i>nfind</i> <i>notfind</i>	Select Lines by XEDIT NFind Logic <pre> ▶---+-NFIND---+--+-----+-----▶ +-NOTFIND-+ +--string--+ </pre>
<i>ninside</i> <i>notinsid</i> <i>notinside</i> 3.09	Select Records Not between Labels <pre> ▶---+-NINSIDE-----+--+-----+-----+delimitedString+number-----+▶ +-NOTINSIDE--+ +-ANYcase-----+ +-delimitedString+ +-CASEANY-----+ +-IGNORECASE--+ +-CASEIGNORE--+ +-CASELESS-----+ </pre>
<i>nlocate</i> <i>notlocate</i>	Select Lines that Do Not Contain a String <pre> ▶---+-NLOCATE-----+--+-----+-----+-----+-----+-----+▶ +-NOTLOCATE--+ +-ANYCase-----+ +-MIXED- (1)-+ +-inputRanges--+ +-CASEANY-----+ +-ONEs-- (1)-+ +-CASEIGNORE--+ +-ZEROs- (1)-+ +-IGNORECASE--+ +-CASELESS-----+ </pre> <pre> ▶-----+--+-----+-----+▶ +-ANYof--+ +-delimitedString+ </pre> <ul style="list-style-type: none"> (1) Not in NetRexx Pipelines, yet.
<i>noEofBack</i>	Pass Records and Ignore End-of-file on Output <pre> ▶---NOEOFBACK-----▶ </pre>

<p><i>nop</i></p>	<p>No Operation</p> <p>NetRexx</p> <pre>▶▶--NOP-----▶◀</pre> <ul style="list-style-type: none"> • Pipes for NetRexx only.
<p><i>not</i></p>	<p>Run Stage with Output Streams Inverted</p> <pre>▶▶--NOT--stage--+-----+-----▶◀ +--operands--+</pre>
<p><i>notfind</i> <i>nfind</i></p>	<p>Select Lines by XEDIT NFind Logic</p> <pre>▶▶---+NOTFIND---+-----+-----▶◀ +-NFIND---+ +--string--+</pre>
<p><i>notin</i> <i>notin</i> <i>notin</i> <i>ninside</i></p>	<p>Select Records Not between Labels</p> <pre>▶▶+NOTINSIDE---+-----+-----+delimitedString+number-----+▶◀ +-NINSIDE----+ +-ANYcase----+ +-delimitedString+ +-CASEANY----+ +-IGNORECASE--+ +-CASEIGNORE--+ +-CASELESS----+</pre>
<p><i>notlocate</i> <i>nlocate</i></p>	<p>Select Lines that Do Not Contain a String</p> <pre>▶▶+NOTLOCATE---+-----+-----+-----+-----+-----▶◀ +-NLOCATE---+ +-ANYCase----+ +-MIXED- (1)-+ +-inputRanges+ +-CASEANY----+ +-ONEs-- (1)-+ +-CASEIGNORE--+ +-ZEROs- (1)-+ +-IGNORECASE--+ +-CASELESS----+</pre> <pre>▶+-----+-----+-----+▶◀ +-ANYof+ +-delimitedString+</pre> <ul style="list-style-type: none"> • (1) Not in NetRexx Pipelines, yet.
<p><i>nuext</i></p>	<p>Call a Nucleus Extension</p> <ul style="list-style-type: none"> • Not implemented in Netrex Pipelines.
<p><i>optcdj</i></p>	<p>Generate Table Reference Character (TRC)</p> <ul style="list-style-type: none"> • Not implemented in Netrex Pipelines.
<p><i>outside</i></p>	<p>Select Records Not between Labels</p> <pre>▶▶--OUTSIDE+-----+delimitedString+number-----+▶◀ +-ANYcase----+ +-delimitedString+ +-CASEANY----+ +-CASEIGNORE--+ +-IGNORECASE--+ +-CASELESS----+</pre>
<p><i>outstore</i></p>	<p>Unload a File from a storage Buffer</p> <ul style="list-style-type: none"> • Not implemented in Netrex Pipelines.
<p><i>over</i></p>	<p>Write the Values of Stems</p> <ul style="list-style-type: none"> • Obsolete. Now use varover. over is now an alias for overlay..

<p><i>overlay</i> <i>overla</i> <i>overl</i> <i>over</i></p>	<p>Overlay Data from Input Streams</p> <div data-bbox="279 129 1369 443" style="border: 1px solid black; padding: 10px;"> <pre> +-NOHOLD-(1)-+ +-PAD-(1)+ +-BLANK-----+ ▶▶--OVERlay-----+-----+-----+-----▶ +-HOLD-(1)---+ +-xorc-----+ +-SPACE-(1)+ ▶+-----+-----+-----+-----▶ +-TRANSPARENT+-xorc---(1)+ +-STRING--delimitedString-(1)(2)+ +-BLANK-+ +-SPACE-+ </pre> </div> <ul style="list-style-type: none"> • HOLD keeps the last record from each stream, except primary, and uses it if the stream ends. • TRANSPARENT means that character can be different from the PAD character. If omitted, it is the same as PAD character. • dstream can be used instead of a non-primary stream. • (1) NetRexx Pipelines only • (2) same as highest (+1) stream; implies HOLD
<p><i>overstr</i></p>	<p>Process Overstruck Lines</p> <ul style="list-style-type: none"> • Not implemented in Netrex Pipelines.
<p><i>pack</i></p>	<p>Pack Records as Done by XEDIT and COPYFILE</p> <ul style="list-style-type: none"> • Not implemented in Netrex Pipelines.
<p><i>pad</i></p>	<p>Expand Short Records</p> <div data-bbox="279 981 1248 1122" style="border: 1px solid black; padding: 10px;"> <pre> +-Right-+ +-BLANK-+ ▶▶-PAD-+-----+-----+-----+-----number-+-----+-----▶ +-Left--+ +-+-----+MODULO-+ +-xorc--+ +-number-+ </pre> </div>
<p><i>parcel</i></p>	<p>Parcel Input Stream into Records</p> <ul style="list-style-type: none"> • Not implemented in Netrex Pipelines.

pickparse
3.09

Select Lines that Satisfy Relations using Rexx Parse



- Records are parsed via the parse_delimited_string.
- Variables are named \$n, where n is 1 to 9.
- The values of the variables are put into the logic_delimited_string replacing \$n and evaluated. If TRUE, the record is put out on the stream numbered by the dstring's position.
- The stream for a Dstring of ELSE is used if no previous logic Dstring is TRUE.
- If there is no specific ELSE, there is an implied one at the end; if that stream is not connected, the record is discarded.
- If ONE then the record is put out on, at most, one stream: the first one matched.
- If ALL then the record is put out on all streams matched.
- If SINGLE then the records are all put out on the primary output stream.
- The parse_delimited_string and logic_delimited_string(s) follow normal NetRexx rules.
- (1) Implied ELSE after last specified dstring.
- (2) Up to 10 logic_Dstrings may be specified to go to up to 11 output streams (including an implied ELSE).
- Not implemented in CMS Pipelines.

Pickparse permits selecting records by a NetRexx logical expression, using parts of the record selected by a Rexx PARSE template.

A simple example has two delimited strings, a Rexx template and a logical expression:

```
pickparse / . . $3 . 50 $5 +5 / / $3 < $5 /
```

The parse template selects the 3rd word, and the 5 characters starting in column 50. the variable names are a dollar sign and a digit. Then those variables can be used in the logic expression. When run, and records matching the logic expression are written to the primary output stream, others to the secondary. If either stream is not connected, the corresponding records are discarded.

There can be multiple logic expressions, each in its own delimited string. Parenthetical expressions may be used. Records are matched to each in turn. Any records matching are written to that output stream, if connected.

With the option ONE, the default, each record is written to one output stream: the first one it matches. With the option ALL, the matching goes on and a record could be written to multiple output streams.

There is an implicit or explicit ELSE as the last logic expression. Records that have not matched any of the previous expressions match this and are written or discarded depending on if the stream is connected or not.

The parse template can define up to 9 separate zones, \$1 to \$9. The variables \$_n are also available for the logic expressions; they are the values from the previous record. Initially these are "".

There can be up to 10 output streams defined, and up to 9 logic expressions plus ELSE.

pipcmd

Issue Pipeline Commands

- Not implemented in Netrex Pipelines.

pipestop

Terminate Stages Waiting for an External Event

- Not implemented in Netrex Pipelines.

polish

Reverse Polish Expression Parser

- Not implemented in Netrex Pipelines.

predselect
predsel

Control Destructive Test of Records

- Not implemented in Netrex Pipelines.

preface

Put Output from a Device Driver before Data on the Primary Input Stream

- Not implemented in Netrex Pipelines.

<p><i>prefix</i></p>	<p>Stop and Run a Stage First, Before Continuing</p> <div data-bbox="279 123 837 190" style="border: 1px solid black; padding: 5px;"> <pre>NetRexx ▶▶--PREFIX---string-----▶▶</pre> </div> <ul style="list-style-type: none"> • Blocks its primary input and excutes stage supplied as an argument. The output from this stage are put to the primary output stream. When its compete the primary input is shorted. • Not implemented in CMS Pipelines.
<p><i>printmc</i></p>	<p>Print Lines</p> <ul style="list-style-type: none"> • Not implemented in Netrex Pipelines.
<p><i>punch</i></p>	<p>Punch Cards</p> <ul style="list-style-type: none"> • Not implemented in Netrex Pipelines.
<p><i>qpdecode</i></p>	<p>Decode to Quoted-printable Format</p> <ul style="list-style-type: none"> • Not implemented in Netrex Pipelines.
<p><i>qpenode</i></p>	<p>Encode to Quoted-printable Format</p> <ul style="list-style-type: none"> • Not implemented in Netrex Pipelines.
<p><i>qsam</i></p>	<p>Read or Write Physical Sequential Data Set through a DCB</p> <ul style="list-style-type: none"> • Not implemented in Netrex Pipelines.
<p><i>qsort</i></p>	<p>Quick Order Records on Whole Length</p> <div data-bbox="279 952 566 1019" style="border: 1px solid black; padding: 5px;"> <pre>NetRexx ▶▶--QSORT-----▶▶</pre> </div> <ul style="list-style-type: none"> • This sort routine is very basic. It uses sortRexx class, which implements the sortClass interface. To sort objects of classes other than Rexx requires that you implement another sortClass with a name begining with 'sort'. • Not implemented in CMS Pipelines.
<p><i>query</i></p>	<p>Obtain Information From Pipelines</p> <div data-bbox="279 1209 917 1433" style="border: 1px solid black; padding: 10px;"> <pre> +-VERSION-----+ ▶▶--Query-+-----+ +-LEVEL-----+ +-SOURCE- (1) ---+ +-MSGLEVEL- (2) -+ +-MSGLIST- (2) --+ </pre> </div> <ul style="list-style-type: none"> • (1) Not CMS • (2) Not NetRexx Pipelines
<p><i>random</i> 3.09</p>	<p>Generate Pseudorandom Numbers</p> <div data-bbox="279 1601 1125 1747" style="border: 1px solid black; padding: 10px;"> <pre> ▶▶--RANDOM--+-----+-----+-----+-----+-----+-----+-----+-----+ +-*-----+ +-*-----+ +-+max_number--+-----+-----+ +-seed_snumber+ </pre> </div> <ul style="list-style-type: none"> • NetRexx Pipelines will be a different sequence than CMS gives with the same seed.
<p><i>reader</i></p>	<p>Read from a Virtual Card Reader</p> <ul style="list-style-type: none"> • Not implemented in Netrex Pipelines.
<p><i>readpds</i></p>	<p>Read Members from a Partitioned Data Set</p> <ul style="list-style-type: none"> • Not implemented in Netrex Pipelines.

<pre>regex grep 3.09</pre>	<p>Select Lines by a Regular Expression</p> <pre>NetRexx ▶▶---REGEX---+-----+regex_Dstring-(1)---◀◀ +---GREP---+ +-(-- options_string --)-+ options_string: +-----+ ---+-----+--- +-Numbers-----+ (2) +-Before+-1-----+ (3) +-number-+ +-After+-1-----+ (3) +-number-+ +-Context+-1-----+ (4) +-number-+ +-NOseparator-----+ (5) +-Separator+-/--/--+ (5) +-delimitedString-+ +-Tertiary-----+ (6) +-COunt-----+ (7)</pre> <ul style="list-style-type: none"> • NetRexx Pipelines only. • Records matching the RegEx are put out on primary output. • Records not matching are put out on secondary, if connected, or discarded. • . • (1) Regex_string is a Java RegEx expression. Null string passes all records. • (2) Records are prefaced with records number, 10 characters, right justified. • (3) Number of records put out after a matching record. • (4) Number of records put out before and after a matching record. • (5) Inserted before a group of "before records" or the found record with "after records." • (6) Send all matching records (no numbers) to tertiary output stream, if connected. • (7) Only a count of matches is put out on the primary output stream. (Other options probably should not be used with this.)
<pre>retab</pre>	<p>Replace Runs of Blanks with Tabulate Characters</p> <ul style="list-style-type: none"> • Not implemented in NetrexX Pipelines.
<pre>reverse</pre>	<p>Reverse Contents of Records</p> <pre>▶▶---REVERSE---◀◀</pre>
<pre>rexx</pre>	<p>Run a REXX Program to Process Data</p> <ul style="list-style-type: none"> • Not implemented in NetrexX Pipelines.
<pre>rexxvars</pre>	<p>Retrieve Variables from a REXX or CLIST Variable Pool</p> <ul style="list-style-type: none"> • Not implemented in NetrexX Pipelines.
<pre>runpipe</pre>	<p>Issue Pipelines, Intercepting Messages</p> <ul style="list-style-type: none"> • Not implemented in NetrexX Pipelines.
<pre>scm</pre>	<p>Align REXX Comments</p> <ul style="list-style-type: none"> • Not implemented in NetrexX Pipelines.
<pre>sec2greg</pre>	<p>Convert Seconds Since Epoch to Gregorian Timestamp</p> <ul style="list-style-type: none"> • Not implemented in NetrexX Pipelines.

<i>serialize</i>	<p>Convert Objects to/from a Single Text String</p> <p>NetRexx</p> <pre>▶▶--SERIALIZE--++-----+-----▶▶ +--classname- (1) -+</pre> <ul style="list-style-type: none"> • (1) classname if class is specified deserialize input to objects of this type - otherwise serialize input objects. • (2) Pipes for NetRexx only. • (3) For some reason readObject does not like more than one object network in its stream. Block multiple objects. • (4) See examples/serialize_tests01.njp
<i>sfsback</i>	<p>Read an SFS File Backwards</p> <ul style="list-style-type: none"> • Not implemented in Netrex Pipelines.
<i>sfsdirectory</i>	<p>List Files in an SFS Directory</p> <ul style="list-style-type: none"> • Not implemented in Netrex Pipelines.
<i>sfsrandom</i>	<p>Random Access an SFS File</p> <ul style="list-style-type: none"> • Not implemented in Netrex Pipelines.
<i>sfsupdate</i>	<p>Replace Records in an SFS File</p> <ul style="list-style-type: none"> • Not implemented in Netrex Pipelines.
<i>snake</i> <i>3.09</i>	<p>Build Multicolumn Page Layout</p> <pre>▶▶--SNAKE--number_cols--++-----+-----▶▶ +--number_rows--++-----+----- +--page_seperator_DString- (1) -+</pre> <ul style="list-style-type: none"> • (1) NetRexx Pipelines only. Appears first, last, and between pages. Avoid \ as escape terms maybe added in the future. \n for newline is OK. Your system may require \\n .
<i>socka2ip</i>	<p>Format sockaddr_in Structure</p> <ul style="list-style-type: none"> • Not implemented in Netrex Pipelines.

Order Records

```

NetRexx
▶▶--SORT--+-----+-----+-----+-----+-----▶
      |  +-REXX-----+ +-10000-+ | +-inputRange-+
      +-(+-----+-----+-----+)-+
      +-class-(2)+ +-size--+

      +-Ascending-(1)-+
▶--+-----+-----+-----+-----+-----▶
      +-Descending-(1)+ +-SINGLEOK-(3)+
    
```

- (1) May come before inputRange, for backwards compatability.
- (2) Requires that you implement another sortClass with a name beginning with 'sort'
- (3) Suppresses error message if only one record to sort for Rexx objects.
- Uses *sortClass* class as Interface Class for Generic Sort Objects and *sortRexx* class to Sort Rexx Text Objects

```

CMS
▶▶--SORT--+-----+-----+-----+-----+-----▶
      +-NOPAD-----+
      +-COUNT--+ +-PAD-xorc+ +-ANYcase-+
      +-UNIQUE-+

      +-Ascending-----+
▶--+-----+-----+-----+-----+-----▶
      +-Descending-----+
      | +-----+-----+-----+-----+-----+
      | | +-Ascending--+ | |
      +-v-inputRange-+-----+-----+-----+-----+
      +-Descending-+ +-NOPAD-----+
      +-PAD-xorc-+
    
```

Space Words Like REXX

```

(1)
▶▶--SPACE--+-----+-----+-----+-----+-----▶
      +-1-----+ +-BLANK-----+
      +-number-+ +-xorc-----+
      +-----+ +-delimitedString-+
      +-STRING-+

(2)
▶--+-----+-----+-----+-----+-----▶
      +-BLANK-----+
      +-xorc-----+
      | +-ANYof-----+ |
      +-----+ +-delimitedString-+
      +-ALLOf-(3)-+
    
```

- (0) The order is the reverse of CHANGE!
- (1) the replacement char/string
- (2) the char/chars that will be stripped and replaced
- (3) NetRexx Pipelines only, not CMS. The dstring is treated as a single unit for stripping or replacing

Rearrange Contents of Records

Separators
 NetRexx and
 COUNTERS
 comma
 separators

```

+-STOP--ALLEOF----+ (3)
▶--SPECS-----+-----+-----+-----▶
+-STOP--ANYEOF---+ (3) +-COUNTERS-number-+ (12)
+-n-----+ (3)

-----+
▶--+--| Group |-----+-----+-----+-----▶
+-READ-----+ (5) +- (1) ,--+ (4) (13)
+-READSTOP-----+
+-WRITE-----+
+-SELECT-+-streamnum-+-----+
| +-streamid--+ (3)
| +-FIRST-----+
| +-SECOND-----+
+-PAD-+-char-+-----+
| +-hexchar-+
| +-BLANK---+
| +-SPACE---+
+-+WORDSEPARATOR-+-char-+ (7)
+-WS-----+ +-hexchar---+
+-FIELDSEPARATOR- + +-BLANK-----+
+-FS-----+ +-SPACE-----+
| +-TAB-----+
| +-hexstring-+ (4)
| +-qword-----+ (4) (8)

```

Group:
 |--| Id |--| Input |--| Conversion |--| Output |--| Alignment |--+-----+--|
 +---(1)-,---+

Id:
 |-letter-- (2) (14) --:- (1) --|

Input:
 |--+Words- (1) -wnumberrange-----+-----|
 +-Fields- (1) -fnumberrange-----+
 +-cnumberrange-----+
 +-delimitedString-----+
 +-Xhexstring-----+
 +-Hhexstring-----+
 +-Bbinstring-----+
 | +-FROM--1-----+ +-BY--1-----+ |
 +-+RECNO-+-----+-----+-----+-----+
 | +-NUMBER-+ +-FROM--fromnum-+ +-BY--bynum-+ |
 +-TODclock-----+ (3)
 +-.------+ (4) (15)

number or string. Fields identified by a fieldid are accessed as field["id"] when the quotes are required, the id is a single letter, case is respected.

- (11) The data is processed by the toString() method.
- (12) CMS Only. NetRexx ignores COUNTERS n; it has an unlimited number. See the NETREXX converter(10).
- (13) NetRexx Only. A comma may be used to separate groups for readability. It is ignored by the system.
- (14) Letter is a single character, a-zA-Z. Case is respected. BLANK is not permitted between letter and : . The resulting data is available in the NETREXX code as field["letter"].
- (15) NetRexx Only. A "." for input is "0.0", no data is selected. data is "".

Examples:

CMS Pipelines has built into the SPEC stage its own programming language. It is Rexx-like-but-not-quite-Rexx. For NetRexx Pipelines we have built in the worlds best scripting language: NetRexx. This gives all the power, but with a somewhat different syntax, of the CMS version. It is incorporated into the "Conversion" phase, with the key word NETREXX (or NR) and a delimitedString containing the NetRexx source. In running, this code is encapsulated in a method. The data selected in the Input phase is available as the variable data. And whatever is returned is passed to the Output phase of the stage. (As a convenience, if the last statement is not RETURN, the statement "return

spill

Split Long Lines at Word Boundaries

So all of these pipes work the same (giving cba):

split

Split Records Relative to a Target

```

1-* NR /return data.reverse/ 1 | cons"
• pipe "literal abc | spec 1-* NR @rev = data.reverse; return rev@ 1 | cons"
• pipe "literal abc | spec 1-* NR %data = data.reverse% 1 | cons"
▶▶▶ pipe "literal abc | spec /abc/ -NetRexx- /data = data.reverse/ +1 -| cons"
      +-ANYcase-----+ +-MINimum--number--+
Using COUNTERS:
$-CASEANY-----+
+-CASEIGNORE--+
• pipe "literal abc | spec 1-* NR /counter[7]=counter[7]+1;ret=data.reverse
counter[7]+1;return rev@ 1 | cons"
gives cba 1
      +-AT-----+ +-BLANK-----+
Using Field Ids (and "." for output position): In this case the variable data is not used at all! ▶▶
      +------+ +-BEFORE+ +-NOT+ +-| target | +------+
• pipe "literal abc | spec AFTER:1+* . 1 NR @rev = field['T'].reverse; return rev@ 1 |
cons"
target:"literal abc | spec T:1-* . t:1 NR @rev = field['T'].reverse; return rev@ 1 |
cons"
+-xrange-----+
"T:" and "t:" are different.
+-delimitedString--+
+-ANYof-----+
  
```

sql
3.09

Language to SQL

```

• pipe "literal abc | spec T:1-* 6-16, 1.2 NR /rev = field['T'].reverse; return rev/
1.4 | cons"
      +-;-+
▶▶▶ giveSQLba+ abc
      +-(-| options |-)+ +-sql_statement_string-(3)+

options:
-----+
|-----+
| +- /sqlselect.properties/ -+ |
+-PROPERTIES-+- filename_Qword- (7) -----+ (5) +-+
| +-HEADERS-----+ |
+-+ +- (5) (6) -----+
| +-NOHEADERS-+ |
+-COUNT2SECondary- (5) (11) -----+
+-URL-Qword- (5) (7) -----+
+-JDBCDRIVER-Qword- (5) (7) -----+
+-DBMS-Qword- (5) (7) (8) -----+
+-DB_NAME-Qword- (5) (7) (8) -----+
+-USER-Qword- (5) (7) (8) (10) -----+
+-PASS-Qword- (5) (7) (8) (10) -----+
  
```

- uses jdbc to select from any jdbc enabled dbms
- properties file (sqlselect.properties default) is read from the secondary input stream to find jdbcdriver name, url, user, pass
- sample properties file:
- ```

#JDBC driver name
#Tue Feb 03 23:29:43 GMT+01:00 1998
jdbcdriver=com.imaginary.sql.mysql.MysqlDriver
url=jdbc:mysql://localhost:1114/TESTDB
the following are not needed for some DBMS, ex: SQLite

```

```
user=db_user_name
pass=password_for_db
```

- 
- if this file is not found default (compiled in) values are used
- (1) when using a sql select \* (all columns) from the commandline, quote the query as in `java pipes.compiler (query) "sql select * from dept | console"`
- (2) the netrexx/jdbc combination is extremely case sensitive for column and table names
- (3) this sql\_select\_string executed, then statements are read from the primary input stream. this is optional in NetRexx Pipelines only.
- (4) CMS does not use the stream input
- (5) NetRexx Pipelines only
- (6) CMS Pipelines is implied HEADERS only.
- (7) A Qword is an optionally quoted word. If it contains spaces, it must be quoted.
- (8) EXPERIMENTAL Subject to change. DBMS is the kind of database, e.g. SQLite. DB\_name is the file name. These are used in place of URL and JDBC\_DRIVER. SQLite is the only one tested as of 8/15/20.
- (9) the SQLSELECT stage uses HEADERS as the default.
- (10) USER & PASS are needed for some DBMSs and not others, ex. SQLite.
- (11) the count or other output from non-select statements goes to the secondary output stream if connected, or is discarded. Otherwise it goes to the primary.
- 
- Priority order for URL, JDBC\_DRIVER and DBMS, DB\_NAME (first one found rules):
  1. option in the SQL command string
  2. from secondary input stream
  3. from "sql.properties" file or from file specified by PROPERTIES option
  4. Builtin

*sqlcodes*

**Write the last 11 SQL Codes Received**

- Not implemented in Netrexx Pipelines.

|                  |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
|------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <i>sqlselect</i> | <p><b>Query a Database and Format Result</b></p> <pre> ▶--SQLSELECT--++-----+--▶       +-(-  options  -)-+    +-SELECT-+                                     +-;-+ ▶+-----+-----+-----+-----+-----+-----▶       +-sql_select_statement_string-(3)-+  options:   +-----+    -----        +-/sqlselect.properties/-+       +-PROPERTIES-+-filename_Qword-(7)-----+(5)++     +-NOHEADERS-+       +-+             +- (5) (6)-----+     +-HEADERS---+       +-URL-Qword-(5) (7)-----+   +-JDBCDRIVER-Qword-(5) (7)-----+   +-DBMS-Qword-(5) (7) (8)-----+   +-DB_NAME-Qword-(5) (7) (8)-----+   +-USER-Qword-(5) (7) (8) (10)-----+   +-PASS-Qword-(5) (7) (8) (10)-----+ </pre> <ul style="list-style-type: none"> <li>• (1) when using a sqlselect * (all columns) from the commandline, quote the query as in java pipes.compiler (query) "sqlselect * from dept   console"</li> <li>• (2) the netrexx/jdbc combination is extremely case sensitive for column and table names</li> <li>• (3) if no sql_select_string is specified, it is read from the primary input stream. this is optional in NetRexx Pipelines only. CMS does not use the stream input.</li> <li>• (4) a maximum of only one record is ever read from the primary input stream.</li> <li>• (5) NetRexx Pipelines only</li> <li>• (6) CMS Pipelines is implied HEADERS only.</li> <li>• (7) A Qword is an optionally quoted word. If it contains spaces, it must be quoted.</li> <li>• (8) EXPERIMENTAL Subject to change. DBMS is the kind of database, e.g. SQLite. DB_name is the file name. These are used in place of URL and JDBCDRIVER. SQLite is the only one tested as of 8/15/20.</li> <li>• (9) the SQL stage uses NOHEADERS as the default.</li> <li>• (10) USER &amp; PASS are needed for some DBMSs and not others, ex. SQLite.</li> <li>• Priority order for URL, JDBCDRIVER, DBMS, DB_NAME, USER, &amp; PASS (first one found rules):       <ol style="list-style-type: none"> <li>1. option in the SQL command string</li> <li>2. from secondary input stream</li> <li>3. from "sqlselect.properties" file or from file specified by PROPERTIES option</li> <li>4. Builtin</li> </ol> </li> </ul> |
| <i>stack</i>     | <p><b>Read or Write the Program Stack</b></p> <ul style="list-style-type: none"> <li>• Not implemented in Netrexx Pipelines.</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| <i>starmon</i>   | <p><b>Write Records from the *MONITOR System Service</b></p> <ul style="list-style-type: none"> <li>• Not implemented in Netrexx Pipelines.</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
| <i>starmsg</i>   | <p><b>Write Lines from a CP System Service</b></p> <ul style="list-style-type: none"> <li>• Not implemented in Netrexx Pipelines.</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
| <i>starsys</i>   | <p><b>Write Lines from a Two-way CP System Service</b></p> <ul style="list-style-type: none"> <li>• Not implemented in Netrexx Pipelines.</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
| <i>state</i>     | <p><b>Provide Information about CMS Files</b></p> <ul style="list-style-type: none"> <li>• Not implemented in Netrexx Pipelines.</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
| <i>state</i>     | <p><b>Verify that Data Set Exists</b></p> <ul style="list-style-type: none"> <li>• Not implemented in Netrexx Pipelines.</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| <i>statew</i>    | <p><b>Provide Information about Writable CMS Files</b></p> <ul style="list-style-type: none"> <li>• Not implemented in Netrexx Pipelines.</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |

|                                                                                 |                                                                                                                                                                                                                                                                                                                                                                                                                            |
|---------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <i>stem</i>                                                                     | <p><b>Retrieve or Set Variables in a REXX or CLIST Variable Pool</b></p> <p><b>NetRexx</b></p> <pre>▶--STEM--stem-----▶</pre> <p><b>CMS</b></p> <pre>▶--STEM--stem-+-----+-----+-----+-----▶                 +-PRODUCER-+ +-number-+ +-NOMSG233-+                 +-MAIN-----+                 +-SYMBOLIC-+ ▶+-----+-----+-----+-----▶                 +-DIRECT----+ +-APPEND-----+                 +-FROM--number-+</pre> |
| <i>stfle</i>                                                                    | <p><b>Store Facilities List</b></p> <ul style="list-style-type: none"> <li>• Not implemented in Netrex Pipelines.</li> </ul>                                                                                                                                                                                                                                                                                               |
| <i>storage</i>                                                                  | <p><b>Read or Write Virtual Machine Storage</b></p> <ul style="list-style-type: none"> <li>• Not implemented in Netrex Pipelines.</li> </ul>                                                                                                                                                                                                                                                                               |
| <i>strasmfind</i>                                                               | <p><b>Select Statements from an Assembler File as XEDIT Find</b></p> <ul style="list-style-type: none"> <li>• Not implemented in Netrex Pipelines.</li> </ul>                                                                                                                                                                                                                                                              |
| <i>strasmnfind</i>                                                              | <p><b>Select Statements from an Assembler File as XEDIT NFind</b></p> <ul style="list-style-type: none"> <li>• Not implemented in Netrex Pipelines.</li> </ul>                                                                                                                                                                                                                                                             |
| <i>strfind</i>                                                                  | <p><b>Select Lines by XEDIT Find Logic</b></p> <pre>▶-----STRFIND--+-+-----+---delimitedString-----▶                 +-ANYcase----+                 +-CASEANY----+                 +-IGNORECASE-+                 +-CASEIGNORE-+                 +-CASELESS---+</pre>                                                                                                                                                      |
| <i>strfrlabel</i><br><i>strfrlabe</i><br><i>strfrlab</i><br><i>strfromlabel</i> | <p><b>Select Records from the First One with Leading String</b></p> <pre>                +--STRFROMLABEL--+                +-INCLUSIVE-+ ▶--+-STRFRLABEL-----+-----+-----+-----+delimitedString--▶                 +-ANYcase----+ +-EXCLUSIVE-+                 +-CASEANY----+                 +-IGNORECASE-+                 +-CASEIGNORE-+                 +-CASELESS---+</pre>                                          |
| <i>strfromlabel</i><br><i>strfrlabel</i><br><i>strfrlabe</i><br><i>strfrlab</i> | <p><b>Select Records from the First One with Leading String</b></p> <pre>                +--STRFRLABEL-----+                +-INCLUSIVE-+ ▶--+-STRFROMLABEL--+-+-----+-----+-----+delimitedString--▶                 +-ANYcase----+ +-EXCLUSIVE-+                 +-CASEANY----+                 +-IGNORECASE-+                 +-CASEIGNORE-+                 +-CASELESS---+</pre>                                        |

*strip*

### Remove Leading or Trailing Characters

```

 +-BOTH-----+
▶▶--STRIP--+-----+--+-----+--+-----+▶▶
 +-| case |--+ +-LEADING--+ +-TO--+
 +-TRAILING--+ +-NOT--+

 +-BLANK-----+
▶▶--+-----+▶▶
 +-| target |--+-----+
 +-number--+ (1)

case:
|--+-----+--|
 +-ANYCase-----+
 +-CASEANY-----+
 +-CASEIGNORE--+
 +-IGNORECASE--+
 +-CASELESS-----+

target:
|--+-----+--|
 +-+--xrange-----+--|
 +-+--STRing--+--delimitedString--+
 +-ANYof--+

```

- (1) Not implemented in Netrexx Pipelines.

*strliteral*  
*strlitera*  
*strliter*  
*strlite*  
*strlit*

### Write the Argument String

```

▶▶--STRLITeral--+-----+--+-----+▶▶
 | +-PREFACE--+ | +-delimitedString+
 +-+-----+--+-----+
 | +-APPEND--+ +-CONDitional+ |
 +-IFEMPTY-----+

```

*strnfind*

### Select Lines by XEDIT NFind Logic

```

▶▶--STRNFIND--+-----+delimitedString-----▶▶
 +-ANYcase-----+
 +-CASEANY-----+
 +-IGNORECASE--+
 +-CASEIGNORE--+
 +-CASELESS-----+

```

*strtolabel*  
*strtolabe*  
*strtolab*

### Select Records to the First One with Leading String

```

 +-INCLUSIVE--+
▶▶--STRTOLABel--+-----+--+-----+delimitedString-----▶▶
 +-ANYcase-----+ +-EXCLUSIVE+
 +-CASEANY-----+
 +-IGNORECASE--+
 +-CASEIGNORE--+
 +-CASELESS-----+

```

*structure*  
*struct*

### Manage Structure Definitions

- Not implemented in Netrexx Pipelines.

|                                                                                                                                                          |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
|----------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <p><i>strwhilelable</i><br/> <i>strwhilelabl</i><br/> <i>strwhilelab</i><br/> <i>strwhilela</i><br/> <i>strwhilel</i><br/> <i>strwhile</i><br/> 3.09</p> | <p><b>Select Run of Records with Leading String</b></p> <div style="border: 1px solid black; padding: 10px; margin: 10px 0;"> <pre style="font-family: monospace;">                 +-INCLUSIVE-+ ▶▶--STRWHILElabel--+-----+-----+delimitedString--&lt;&lt;                 +-ANYcase-----+ +-EXCLUSIVE-+                 +-CASEANY-----+                 +-IGNORECASE-+                 +-CASEIGNORE-+                 +-CASELESS-----+             </pre> </div>                                                                                                                                                                                                       |
| <p><i>stsi</i></p>                                                                                                                                       | <p><b>Store System Information</b></p> <ul style="list-style-type: none"> <li>• Not implemented in Netrexx Pipelines.</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
| <p><i>subcom</i></p>                                                                                                                                     | <p><b>Issue Commands to a Subcommand Environment</b></p> <ul style="list-style-type: none"> <li>• Not implemented in Netrexx Pipelines.</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| <p><i>substring</i><br/> <i>substr</i></p>                                                                                                               | <p><b>Write substring of record</b></p> <ul style="list-style-type: none"> <li>• Not implemented in Netrexx Pipelines.</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| <p><i>synchronise</i><br/> <i>sync</i><br/> <i>synchronize</i></p>                                                                                       | <p><b>Synchronise Records on Multiple Streams</b></p> <ul style="list-style-type: none"> <li>• Not implemented in Netrexx Pipelines.</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
| <p><i>synchronize</i><br/> <i>sync</i><br/> <i>synchronise</i></p>                                                                                       | <p><b>Synchronise Records on Multiple Streams</b></p> <ul style="list-style-type: none"> <li>• Not implemented in Netrexx Pipelines.</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
| <p><i>sysdsn</i></p>                                                                                                                                     | <p><b>Test whether Data Set Exists</b></p> <ul style="list-style-type: none"> <li>• Not implemented in Netrexx Pipelines.</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| <p><i>sysout</i></p>                                                                                                                                     | <p><b>Write System Output Data Set</b></p> <ul style="list-style-type: none"> <li>• Not implemented in Netrexx Pipelines.</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| <p><i>sysvar</i></p>                                                                                                                                     | <p><b>Write System Variables to the Pipeline</b></p> <ul style="list-style-type: none"> <li>• Not implemented in Netrexx Pipelines.</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| <p><i>tag</i><br/> 3.11</p>                                                                                                                              | <p><b>Surrounds Input Records with a HTML tag and its End Tag</b></p> <div style="border: 1px solid black; padding: 10px; margin: 10px 0;"> <pre style="font-family: monospace;"> NetRexx ▶▶--TAG--word--+-----+-----&lt;&lt;                 +-string--+             </pre> </div> <ul style="list-style-type: none"> <li>• Outputs a record: &lt;word string&gt;, then passes through all records on its primary input, and finally a record: &lt;/word&gt;.</li> </ul>                                                                                                                                                                                                |
| <p><i>tags</i><br/> 3.11</p>                                                                                                                             | <p><b>Surrounds Input Records with HTML tags and their End Tags</b></p> <div style="border: 1px solid black; padding: 10px; margin: 10px 0;"> <pre style="font-family: monospace;"> NetRexx ▶▶--TAGS----delimitedString--+-----+-----&lt;&lt;                  -----+-----                  +-+delimitedString-+-+             </pre> </div> <ul style="list-style-type: none"> <li>• Outputs a record for each delimitedString: &lt;delimitedString&gt;, then passes through all records on its primary input, and finally a record for each, in reverse order: &lt;/first_word_of_delimitedString&gt;.</li> <li>• Any delimitedString may be a single word.</li> </ul> |

|                 |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
|-----------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <i>take</i>     | <p><b>Select Records from the Beginning or End of the File</b></p> <div data-bbox="279 129 1292 302" style="border: 1px solid black; padding: 5px; margin: 10px 0;"> <pre>       +-FIRST-+  +-1-----+ ▶▶--TAKE--+-+-----+-----+-----+-----+-----▶▶       +-LAST--+  +-number-----+ +-BYTEs (1) -+                     +-snumber (2) -+                     +-*-----+ </pre> </div> <ul style="list-style-type: none"> <li>• (1) CMS must be BYTES</li> <li>• (2) Not CMS; NetRexx Pipelines: minus reverses first/last</li> </ul> |
| <i>tape</i>     | <p><b>Read or Write Tapes</b></p> <ul style="list-style-type: none"> <li>• Not implemented in Netrex Pipelines.</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                        |
| <i>tcpchsum</i> | <p><b>Compute One's complement Checksum of a Message</b></p> <ul style="list-style-type: none"> <li>• Not implemented in Netrex Pipelines.</li> </ul>                                                                                                                                                                                                                                                                                                                                                                             |

```

▶▶--TCPCLIENT--IPaddress--number--▶
+-----+
▶-----▶▶
+-| Deblock |-----+
+-EMSGSF4- (1) -----+
+-GETSOCKName- (1) -----+
+-GREETING-----+
+-KEEPALIVE-----+
+-LINGER--number-----+
| +-ANY-----+ |
+-LOCALIPaddress--+-HOSTID-----+ (1) -----+
| +-IPaddress--+ |
+-LOCALport--number- (1) -----+
+-NODELAY- (2) -----+
+-ONERESPONSE-----+
+-OOBINLINE- (1) -----+
+-REUSEADDR- (1) -----+
+-SECURE-+-+-----+-+-----+- (1) -----+
| +-GETSECINFO-+ +-SAFE----+ |
| +-UNSAFE-+ |
+-SF- (1) -----+
+-SF4- (1) -----+
+-STATistics- (1) -----+
+-TIMEOUT--number-----+
+-USERid--word- (1) -----+

Deblock:
|--DEBLOCK--+-CRLF-----+▶
| +-LINEND-+-----+
| +-xorc-+ |
+-SF-----+
+-SF4-----+
+-STRING--delimitedString-+

▶-----+--|
+-GROUP--delimitedString--+

```

- (1) CMS Pipelines Only.
- (2) NetRexx Pipelines Only.

The options implemented are similar to the CMS definition.

- linger - wait a bit before terminating the last read (units SECONDS)
- timeout - wait this long before timing reads out (units MS)
- deblock - If deblock is omitted a copy stage is used.
- group - similar to CMS. A delimited string containing a stage is expected. You can use a run of stages, but its dangerous since you to know the stage sep character being used...
- greeting - expect a greeting message and discard it
- nodelay - use the nodelay option
- keepalive - enable keep alive socket option
- onerresponse - synchronize cmds/replys

tcpdata

### Read from and Write to a TCP/IP Socket

```

-----+
>>--TCPDATA--+-+-----+<<
 +-| Deblock |-----+
 +-GETSOCKName- (1)-----+
 +-GREETING- (1)-----+
 +-KEEPALIVE- (1)-----+
 +-LINGER--number-----+
 +-NODELAY- (2)-----+
 +-ONERESPONSE-----+
 +-OOBINLINE- (1)-----+
 +-REUSEADDR- (1)-----+
 +-SF- (1)-----+
 +-SF4- (1)-----+
 +-+--SECURE-----+(1)+
 | +-TLSLABEL--word-+ |
 +-STATistics- (1)-----+
 +-TIMEOUT- (2)-----+

Deblock:
| --DEBLOCK--+-+--CRLF-----+-->
 +--LINEND-+-----+
 | +-xor-+ |
 +--SF-----+
 +--SF4-----+
 +--STRING--delimitedString-+

>>+-----+-----|
 +-GROUP--delimitedString-+

```

- Simple tcpdata implementation.
- (1) CMS Pipelines Only
- (2) NetRexx Pipelines Only
  - linger - wait a bit before terminating the last read (units SECONDS)
  - timeout - wait this long before timing reads out (units MS)
  - deblock - If deblock is omitted a copy stage is used.
  - group - similiar to cms. A delimited string containing a stage is expected. You can use a run of stages, but its is dangerous since you to know the stage sep character being used...
  - nodelay - use the nodelay option
  - onerresponse - synchronize requests/replies

tcplisten

### Listen on a TCP Port

```

-----+
>>--TCPLISTEN--number--+-+-----+<<
 +-BACKLOG--number-----+
 +-GETSOCKName- (2)-----+
 | +-ANY-----+ |
 +-LOCALIPaddress-+HOSTID----+ (2) -+
 | +-IPaddress-+ |
 +-REUSEADDR- (2)-----+
 +-STATistics- (2)-----+
 +-USERid--word- (2)-----+
 +-TIMEOUT--number- (1)-----+

```

- (1) NetRexx Pipelines only.
- (2) CMS Pipelines only.
- Simple tcplisten implementation. You can only supply the port and a timeout value. Its ignored unless tcplisten's output stream has been severed, in which case tcplisten terminates.
- If input stream 0 is connected, tcplisten does a peekto before calling the accept method. The object is consumed after the output of the socket object returns.

terminal  
 termina  
 termina  
 termin  
 termi  
 term  
 console  
 consol  
 conso  
 cons  
 cons  
 3.11

### Read or Write the Terminal in Line Mode

```

▶---+--TERMinal--+---+-----+-----+-----+-----+-----+-----▶
 +-CONSOLE--+ +-EOF--delimitedString+ +-PREFIX--+delimitedString-(1)+
 +-NOEOF-----+ +-PROMPT--+

▶---+-----+-----+-----▶
 +-DIRECT-(2)-----+
 +-ASYNchronously-(2)+
 +-DARK-(2)-----+

```

- (1) NetRexx only  
 On first stage, delimitedString is put out as a prompt  
 On other stages, each line is prefixed with delimitedString  
 Output to next stage does NOT include delimitedString  
 Either keyword can be used for either stage
- (2) CMS only

threeway

### Split record three ways

- Not implemented in Netrex Pipelines.

timestamp  
 timestam  
 timesta  
 timest  
 times  
 time

### Prefix the Date and Time to Records

```

▶---+-----+-----+-----+-----+-----+-----▶
 (1) (2)
 | | +-8-----+ | |
 | +--+number+--+--+ |
 | +-number-+ |
 +-SHORTdate-----+ (3/09/46 23:59:59)
 +-ISODate-----+ (1946-03-09 23:59:59)
 +-FULLdate-----+ (3/09/1946 23:59:59)
 +-STANDARD-----+ (19460309235959)
 +-STRING--delimitedString--(3)---+

```

- (1) First character, from right, to include, <= 16
- (2) Count of characters to include. <= 16 - (1). Default = (1)
- (3)
  - %% A single %.
  - %Y Four digits year including century (0000-9999).
  - %y Two-digit year of century (00-99).
  - %m Two-digit month (01-12).
  - %n Two-digit month with initial zero changed to blank ( 1-12).
  - %d Two-digit day of month (01-31).
  - %e Two-digit day of month with initial zero changed to blank ( 1-31).
  - %j Julian day of year (001-366).
  - %H Hour, 24-hour clock (00-23).
  - %k Hour, 24-hour clock with leading zero blank ( 0-23).
  - %M Minute (00-59).
  - %S Second (00-60).
  - %F Equivalent to %Y-%m-%d (the ISO 8601 date format).
  - %T Short for %H:%M:%S.
  - %t Tens and hundredth of a second (00-99).

tokenise  
 tokenize

### Tokenise Records

```

▶---+-----+-----+-----+-----+-----+-----▶
 +-//- (1)-----+
 +-TOKENISE--+---+-----+-----+-----+-----+-----▶
 +-TOKENIZE--+ +-delimitedString-(1)-+ +-delimitedString-+

```

- (1) In CMS Pipelines, the first delimited string is required. In NetRexx Pipelines, it defaults to // if no second string.

|                                                          |                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
|----------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <p><i>tokenize</i><br/><i>tokenise</i></p>               | <p><b>Tokenise Records</b></p> <div style="border: 1px solid black; padding: 5px; margin: 10px 0;"> <pre style="text-align: center;">+--//-(1)-----+ ▶--+-TOKENIZE-+-+-----+-----+-----+-----▶ +--TOKENISE--+ +--delimitedString-(1)-+ +--delimitedString-+</pre> </div> <ul style="list-style-type: none"> <li>• (1) In CMS Pipelines, the first delimited string is required. In NetRexx Pipelines, it defaults to // if no second string.</li> </ul> |
| <p><i>tolabel</i><br/><i>tolabe</i><br/><i>tolab</i></p> | <p><b>Select Records to the First One with Leading String</b></p> <div style="border: 1px solid black; padding: 5px; margin: 10px 0;"> <pre style="text-align: center;">▶--TOLABel--+-+-----+-----▶ +--string--+</pre> </div>                                                                                                                                                                                                                           |
| <p><i>totarget</i></p>                                   | <p><b>Select Records to the First One Selected by Argument Stage</b></p> <div style="border: 1px solid black; padding: 5px; margin: 10px 0;"> <pre style="text-align: center;">▶--TOTARGET---stage--+-+-----+-----▶ +--operands---+</pre> </div>                                                                                                                                                                                                        |
| <p><i>trackblock</i></p>                                 | <p><b>Build Track Record</b></p> <ul style="list-style-type: none"> <li>• Not implemented in Netrex Pipelines.</li> </ul>                                                                                                                                                                                                                                                                                                                               |
| <p><i>trackdeblock</i></p>                               | <p><b>Deblock Track</b></p> <ul style="list-style-type: none"> <li>• Not implemented in Netrex Pipelines.</li> </ul>                                                                                                                                                                                                                                                                                                                                    |
| <p><i>trackread</i></p>                                  | <p><b>Read Full Tracks from ECKD Device</b></p> <ul style="list-style-type: none"> <li>• Not implemented in Netrex Pipelines.</li> </ul>                                                                                                                                                                                                                                                                                                                |
| <p><i>tracksquish</i></p>                                | <p><b>Squish Tracks</b></p> <ul style="list-style-type: none"> <li>• Not implemented in Netrex Pipelines.</li> </ul>                                                                                                                                                                                                                                                                                                                                    |
| <p><i>trackverify</i></p>                                | <p><b>Verify Track Format</b></p> <ul style="list-style-type: none"> <li>• Not implemented in Netrex Pipelines.</li> </ul>                                                                                                                                                                                                                                                                                                                              |
| <p><i>trackwrite</i></p>                                 | <p><b>Write Full Tracks to ECKD Device</b></p> <ul style="list-style-type: none"> <li>• Not implemented in Netrex Pipelines.</li> </ul>                                                                                                                                                                                                                                                                                                                 |
| <p><i>trackxpan</i></p>                                  | <p><b>Unsquish Tracks</b></p> <ul style="list-style-type: none"> <li>• Not implemented in Netrex Pipelines.</li> </ul>                                                                                                                                                                                                                                                                                                                                  |

*translate*  
*translat*  
*transla*  
*transl*  
*trans*  
*xlate*

### Transliterate Contents of Records

```
▶---+---TRANSLate---+---+-----+---+-----▶
 +---XLATE-----+ +---inputRange-----+ +-| default-table |--+
 | ↖-----+ |
 +---(-+---inputRange---+)-+

↖-----+
▶---+---+-----+---+-----▶
 +---xrange--xrange--+

default-table:
|---+---UPper-- (1) -----+-----|
 +---LOWer-- (1) -----+-----+
 +---A2E---- (2) -----+-----+
 +---E2A---- (2) -----+-----+
 +---INput-- (3) -----+-----+
 +---OUTput- (3) -----+-----+
 +---+---TO---+---+-----+---n-- (3) ---+
 +---FROM--+ +---CODEPAGE--+
```

Notes:

- (1) UTF-16 (ASCII) in NJPipes, probably EBCDIC in CMS.
- (2) In Netrex Pipelines. EBCDIC to ASCII or ASCII to EBCDIC. Maybe in CMS, the documentation is unclear.
- (3) Not yet in NetRex Pipelines
- [4] NetRex Pipelines only: The secondary input stream is not yet supported.

*trfread*

### Read a Trace File

- Not implemented in Netrex Pipelines.

*truncate*  
*truncat*  
*trunca*  
*trunc*  
*chop*

### Truncate the Record

```
 +---80-----+
▶---+---TRUNCate+---+-----+---+-----▶
 +---CHOP-----+ +---snumber-----|
 +---| stringtarget |--+

stringtarget:
|---+---+-----+---+-----+---+-----+---+-----| target |--|
 +---ANYcase-----+ | +---BEFORE--+ | +---NOT--+
 +---CASEANY-----+ +---+-----+---+-----+---+
 +---CASEIGNORE--+ +---snumber--+ +---AFTER--+
 +---IGNORECASE--+
 +---CASELESS-----+

target:
|---+---xrange-----+---+-----|
 +---+---STRING--+---delimitedString--+
 +---ANYof--+
```

*tso*

### Issue TSO Commands, Write Response to Pipeline

- Not implemented in Netrex Pipelines.

*udp*

### Read and Write an UDP Port

- Not implemented in Netrex Pipelines.

|                                                       |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
|-------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <p><i>unique</i><br/><i>uniqu</i><br/><i>uniq</i></p> | <p><b>Discard or Retain Duplicate Lines</b></p> <pre>       +--NOPAD-----+ ▶--UNIQUE-----+-----+-----+-----+-----▶       +--COUNT--+ +--PAD--xorc--+ +--ANYcase-----+                                       +--CASEANY-----+                                       +--CASEIGNORE--+                                       +--IGNORECASE--+                                       +--CASELESS-----+        +--LAST-----+ ▶-----+-----+-----+-----+-----▶       +--  uniqueRanges  -+ +--SINGLEs-----+                                       +--FIRST-----+                                       +--MULTiple--+                                       +--PAIRwise--+  uniqueRanges:  ---+--inputRange-----+---   -----+-----+-----+-----+-----  +-- (--+--inputRange--+-----+---)---+                                       +--NOPAD-----+                                       +--PAD--xorc--+ </pre> |
| <p><i>unpack</i></p>                                  | <p><b>Unpack a Packed File</b></p> <ul style="list-style-type: none"> <li>• Not implemented in Netrexx Pipelines.</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| <p><i>untab</i></p>                                   | <p><b>Replace Tabulate Characters with Blanks</b></p> <ul style="list-style-type: none"> <li>• Not implemented in Netrexx Pipelines.</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| <p><i>unzip</i></p>                                   | <p><b>Extract Files From a ZIP Archive</b></p> <div data-bbox="279 1048 791 1137" style="border: 1px solid black; padding: 5px;"> <pre> NetRexx &gt;&gt;--UNZIP--+-----+---&lt;&lt;       +--filename- (1) -+ </pre> </div> <p>Notes:</p> <ul style="list-style-type: none"> <li>• (1) If filename is not specified, it is read from the primary input stream. Succeeding input objects are ignored.</li> <li>• The extracted file names are passed to the primary output stream.</li> <li>• Any existing files will be replaced.</li> <li>• This is NetRexx Pipelines only.</li> </ul>                                                                                                                                                                                                                                                                                                                |
| <p><i>update</i></p>                                  | <p><b>Apply an Update File</b></p> <ul style="list-style-type: none"> <li>• Not implemented in Netrexx Pipelines.</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| <p><i>urldeblock</i></p>                              | <p><b>Process Universal Resource Locator</b></p> <ul style="list-style-type: none"> <li>• Not implemented in Netrexx Pipelines.</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| <p><i>uro</i></p>                                     | <p><b>Write Unit Record Output</b></p> <ul style="list-style-type: none"> <li>• Not implemented in Netrexx Pipelines.</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| <p><i>utf</i></p>                                     | <p><b>Convert between UTF-8, UTF-16, and UTF-32</b></p> <ul style="list-style-type: none"> <li>• Not implemented in Netrexx Pipelines.</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |

|                        |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
|------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>var</b>             | <p><b>Retrieve or Set a Variable in a REXX or CLIST Variable Pool</b></p> <div data-bbox="279 129 1217 387" style="border: 1px solid black; padding: 5px;"> <pre> ▶▶--VAR--word--++-----+-----+-----▶▶                 +--PRODUCER- (1) -+  +-number- (1) -+                 +--MAIN- (1) -----+                                 +-SYMBOLIC- (1) --+ ▶+-----+-----+-----+-----+-----▶▶   +--NOMSG233- (1) -+  +-DIRECT- (1) ---+  +-TRACKING- (1) --+ </pre> </div> <ul style="list-style-type: none"> <li>• In NetRexx Pipelines, this can only read vars. It must be the first stage in a pipe.</li> <li>• (1) CMS Pipelines only.</li> </ul> |
| <b>vardrop</b>         | <p><b>Drop Variables in a REXX Variable Pool</b></p> <ul style="list-style-type: none"> <li>• Not implemented in Netrexx Pipelines.</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| <b>varfetch</b>        | <p><b>Fetch Variables in a REXX or CLIST Variable Pool</b></p> <ul style="list-style-type: none"> <li>• Not implemented in Netrexx Pipelines.</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| <b>varload</b>         | <p><b>Set Variables in a REXX or CLIST Variable Pool</b></p> <ul style="list-style-type: none"> <li>• Not implemented in Netrexx Pipelines.</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
| <b>varover</b><br>3.09 | <p><b>Write the Values of Stems</b></p> <div data-bbox="279 913 684 981" style="border: 1px solid black; padding: 2px;"> <p>NetRexx</p> <pre>▶▶--VAROVER--varName---▶▶</pre> </div> <ul style="list-style-type: none"> <li>• NetRexx Pipelines only; not CMS Pipelines</li> <li>• If the secondary output stream is connected, the root is passed on it.</li> </ul>                                                                                                                                                                                                                                                                             |
| <b>varset</b>          | <p><b>Set Variables in a REXX or CLIST Variable Pool</b></p> <ul style="list-style-type: none"> <li>• Not implemented in Netrexx Pipelines.</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
| <b>vchar</b>           | <p><b>Recode Characters to Different Length</b></p> <ul style="list-style-type: none"> <li>• Not implemented in Netrexx Pipelines.</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| <b>vector</b>          | <p><b>Read or Write an Array of Vectors</b></p> <div data-bbox="279 1361 611 1429" style="border: 1px solid black; padding: 2px;"> <p>NetRexx</p> <pre>▶▶--VECTOR--name--▶▶</pre> </div> <ul style="list-style-type: none"> <li>• Pipes for NetRexx only.</li> </ul>                                                                                                                                                                                                                                                                                                                                                                            |
| <b>vectora</b>         | <p><b>Add to an Array of Vectors</b></p> <div data-bbox="279 1563 627 1630" style="border: 1px solid black; padding: 2px;"> <p>NetRexx</p> <pre>▶▶--VECTORA--name--▶▶</pre> </div> <ul style="list-style-type: none"> <li>• Pipes for NetRexx only.</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                  |
| <b>vectorr</b>         | <p><b>Read From an Array of Vectors</b></p> <div data-bbox="279 1765 627 1832" style="border: 1px solid black; padding: 2px;"> <p>NetRexx</p> <pre>▶▶--VECTORR--name--▶▶</pre> </div> <ul style="list-style-type: none"> <li>• Pipes for NetRexx only.</li> </ul>                                                                                                                                                                                                                                                                                                                                                                               |
| <b>vectorw</b>         | <p><b>Write to an Array of Vectors</b></p> <div data-bbox="279 2011 627 2078" style="border: 1px solid black; padding: 2px;"> <p>NetRexx</p> <pre>▶▶--VECTORW--name--▶▶</pre> </div> <ul style="list-style-type: none"> <li>• Pipes for NetRexx only.</li> </ul>                                                                                                                                                                                                                                                                                                                                                                                |



*xlate*  
*translate*  
*translat*  
*transla*  
*transl*  
*trans*

**Transliterate Contents of Records**

```

▶---+--XLATE-----+--+-----+--+-----▶
 +--TRANSlate--+ +--inputRange-----+ +-| default-table |--+
 | ←-----+ |
 +--(-+--inputRange--+)--+

 ←-----+
▶---+--+-----+--+-----▶
 +--xrange--xrange--+

default-table:
|---+--UPper-- (1) -----+-----|
 +--LOWer-- (1) -----+
 +--A2E---- (2) -----+
 +--E2A---- (2) -----+
 +--INput-- (3) -----+
 +--OUTput- (3) -----+
 +--+--TO---+--+-----+--n-- (3) --+
 +--FROM--+ +--CODEPAGE--+

```

**Notes:**

- (1) UTF-16 (ASCII) in NJPipes, probably EBCDIC in CMS.
- (2) In Netrex Pipelines. EBCDIC to ASCII or ASCII to EBCDIC. Maybe in CMS, the documentation is unclear.
- (3) Not yet in NetRex Pipelines
- [4] NetRex Pipelines only: The secondary input stream is not yet supported.

*xmsg*

**Issue XEDIT Messages**

- Not implemented in Netrex Pipelines.

*xpndhi*

**Expand Highlighting to Space between Words**

- Not implemented in Netrex Pipelines.

*xrange*  
 3.09

**Write a Range of Characters**

```

▶---XRANGE--+-----+-----▶
 +-xrange-----|
 +-xorc--xorc+

```

- NetRex uses UTF-16 (ASCII) and CMS uses EBCDIC

*zip*

**Add Files To a new ZIP Archive**

**NetRexx**

```

▶--ZIP--+-----+--▶
 +--name- (1) -+

```

- (1) name is the zip file name. If not provided, the first entry on the primary input stream is used.
- (1) If no extension is provided in name, ".ZIP" is added.
- (1) Any existing file is replaced.
- Subsequent records on the primary input stream are filenames to be added to the Zip archive file.
- File names added passed out on primary out stream.
- NetRexx Pipelines only.

*zone*

**Run Selection Stage on Subset of Input Record**

```

▶--ZONE--+-----+--+-----+--+-----+--+-----+--▶
 +--inputRange--+ +--CASEI--+ +--REVERSE--+
▶--stage--+-----+--▶
 +--operands--+

```

*\_rexx*

**Cast Input and/or Output of a Stage to Type REXX**

**NetRexx**

```

 +--BOTH-----+
▶--_REXX--+-----+--stage--+-----+--▶
 +--IN--+-----+ +--operands--+
 | +--TO--+ |
 +--OUT--+-----+
 +--FROM--+

```

*\_string*

**Cast Input and/or Output of a Stage to Type String**

**NetRexx**

```

 +--BOTH-----+
▶--_STRING--+-----+--stage--+-----+--▶
 +--IN--+-----+ +--operands--+
 | +--TO--+ |
 +--OUT--+-----+
 +--FROM--+

```